

## Specification Sheet

Part Number: 151-03643



No drilling or extra hardware required – just position on steel surface.

Magnetic mounts are reliable even in debris, dirt and oil.

Use for permanent mounting or as a temporary installation tool.

Reuse, 360-degree rotation and reposition capabilities allow for a flexible mounting solution.

Easily remove without leaving residue behind.

Magnetic Clip, Medium, 3/4", Neodymium Magnet/POM/ST, 10lb Pull Force, White, 10/bag

|                |           |
|----------------|-----------|
| Article Number | 151-03643 |
|----------------|-----------|

|      |         |
|------|---------|
| Type | MAGC10M |
|------|---------|

|       |            |
|-------|------------|
| Color | White (WH) |
|-------|------------|

|              |     |
|--------------|-----|
| Quantity Per | bag |
|--------------|-----|

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | Magnetic clips are designed to route bundles by securing to steel surfaces without the need for a mounting hole. Simply attach the wire bundle by pushing it into the clip and position it onto the beam, metal joist, ceiling channel, conveyor frame, or other steel surface. The clips are simple to secure and can attach to surfaces contaminated with oil or debris. Ultra-strong neodymium magnets are ideal as a permanent mount or for temporary applications. Reuse and reposition them for ultimate flexibility without needing to replace or repurchase parts. |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                       |                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------|
| Short Description     | Magnetic Clip, Medium, 3/4", Neodymium Magnet/POM/ST, 10lb Pull Force, White, 10/bag |
| Global Part Name      | MAGC10M-NDFEB35M/POM/ST-WH                                                           |
| Length L (Imperial)   | 1.03                                                                                 |
| Length L (Metric)     | 26.2                                                                                 |
| Fixation Method       | Magnet                                                                               |
| Height H (Imperial)   | 0.97                                                                                 |
| Height H (Metric)     | 24.7                                                                                 |
| Depth D (Imperial)    | 0.23                                                                                 |
| Depth D (Metric)      | 5.7                                                                                  |
| Diameter D (Imperial) | 0.75                                                                                 |
| Diameter D (Metric)   | 19.0                                                                                 |
| Material              | Neodymium alloy 35M (NDFEB35M) Steel (ST) Polyacetal (POM)                           |
| Material Shortcut     | POM ST NDFEB35M                                                                      |
| Halogen Free          | Yes                                                                                  |

|                              |                                  |
|------------------------------|----------------------------------|
| UV Resistant (Yes/No)        | No                               |
| Use Conditions               | For Indoor Use Only              |
| Plenum Rating                | AH-2                             |
| Operating Temperature        | -40°F to +176°F (-40°C to +80°C) |
| Reach Compliant (Article 33) | Yes                              |
| ROHS Compliant               | Yes                              |
| UL Listed (US and Canada)    | Yes                              |
| UL Listed (US)               | Yes                              |
| Package Quantity (Imperial)  | 10                               |
| Package Quantity (Metric)    | 10                               |
| Customs Number               | 8505110070                       |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com