

Specification Sheet

Part Number: 151-04027

No drilling or extra hardware required – just position on steel surface.

Magnetic mounts are reliable even in debris, dirt and oil.

Use for permanent mounting or as a temporary installation tool.

Reuse, 360-degree rotation and reposition capabilities allow for a flexible mounting solution.

Easily remove without leaving residue behind.



Magnetic Clip, Small, 1/2", Neodymium Magnet/POM/ST, 10lb Pull Force, Black, 10/bg

Article Number 151-04027

Type MAGC10S

Color Black (BK)

Quantity Per bag

Product Description

Magnetic clips are designed to route bundles by securing to steel surfaces without the need for a mounting hole. Simply attach the wire bundle by pushing it into the clip and position it onto the beam, metal joist, ceiling channel, conveyor frame, or other steel surface. The clips are simple to secure and can attach to surfaces contaminated with oil or debris. Ultra-strong neodymium magnets are ideal as a permanent mount or for temporary applications. Reuse and reposition them for ultimate flexibility without needing to replace or repurchase parts.

| Short Description | Magnetic Clip, Small, ½", Neodymium Magnet/POM/ST, 10lb Pull Force, Black, 10/bg |
|---------------------------------------|--|
| Global Part Name | MAGC10S-NDFEB35M/POM/ST-BK |
| Length L (Imperial) | 0.62 |
| Length L (Metric) | 15.8 |
| Fixation Method | Magnet |
| Height H (Imperial) Height H (Metric) | 0.73 18.5 |
| Depth D (Imperial) | 0.15 |
| Depth D (Metric) | 3.9 |
| Diameter D (Imperial) | 0.75 |
| Diameter D (Metric) | 19 |
| | |
| Material | Neodymium alloy 35M (NDFEB35M) Polyacetal (POM) Steel (ST) |
| Material Shortcut | NDFEB35M ST POM |

Yes

Halogen Free

Use Conditions For Indoor Use Only

Plenum Rating AH-2

Operating Temperature -40°F to +176°F (-40°C to +80°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

UL Listed (US and Canada) Yes

UL Listed (US) Yes

Package Quantity (Imperial) 10

Package Quantity (Metric) 10

Customs Number 8505110070

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions