

Specification Sheet

Part Number: 156-00459



Versatile design allows cable routing above, perpendicular or parallel to stud.

Can mount up to three bundles simultaneously, making efficient use of a single mounting point.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

PA46 material option allows use in high-heat applications.

2-Piece Cable Tie with Stud Mount, 8.0"L, 5mm Stud Mount, 50lb Tensile Strength, PA66HS/PA66HIRHS, NA/BK, 500/pkg

Article Number	156-00459
Type	T50RSBH5-10
Color	Natural (NA) Black (BK)
Quantity Per	bag

Product Description	Unique, two-piece design allows routing to be above, parallel or perpendicular to stud. This also enables up to three separate bundles to be fastened to the same stud. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.
---------------------	--

Short Description	2-Piece Cable Tie with Stud Mount, 8.0"L, 5mm Stud Mount, 50lb Tensile Strength, PA66HS/PA66HIRHS, NA/BK, 500/pkg
Global Part Name	T50RSBH5-10-PA66HS/PA66HIRHS-NA/BK
Length L (Metric)	200.0
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Metric)	4.6
Bundle Diameter Max (Imperial)	1.77
Bundle Diameter Max (Metric)	45.0
Thickness T (Metric)	1.2
Disc Diameter (Metric)	25.0
Stud Diameter (Metric)	M5 T5
Stud Diamater (Imperial)	0.20

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS PA66HIRHS
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
 Phone: (800) 537-1512 | Email: corp@htamericas.com