

Specification Sheet

Part Number: 156-02482



- Anti-rotation pin eliminates movement of bundle when fastening bolt.
- Heavy duty mount with robust 120 lb tie delivers an ultra strong alternative to metal clamps.
- Assembly withstands vibrations and displacement forces.
- Metal bushing accommodates high tightening torque.

2-Piece Cable Tie with Screw Mount, Unassembled Set, 15" L, M8 Hole, 120lb, PA66HIRHS, Black, 1000/ctn

|                     |                                                                                                                                                                                                                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 156-02482                                                                                                                                                                                                                                                                                                                                                  |
| Type                | T120RCPCM8-TSSET                                                                                                                                                                                                                                                                                                                                           |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                                 |
| Quantity Per        | carton                                                                                                                                                                                                                                                                                                                                                     |
| Product Description | These heavy duty cable tie mounts, secured with mechanical fasteners, include an anti-rotation pin that keeps the mount and harness assembly in position during the torquing of the bolt or nut. They provide an attachment point for securing and routing a single bundle. The mounts provide the highest level of fastening for critical cable security. |
| Short Description   | 2-Piece Cable Tie with Screw Mount, Unassembled Set, 15" L, M8 Hole, 120lb, PA66HIRHS, Black, 1000/ctn                                                                                                                                                                                                                                                     |

|                  |                                           |
|------------------|-------------------------------------------|
| Global Part Name | T120RCPCM8-TSSET-PA66HIRHSUV/PA66HIRHS-BK |
|------------------|-------------------------------------------|

|                                     |     |
|-------------------------------------|-----|
| Minimum Tensile Strength (Imperial) | 120 |
|-------------------------------------|-----|

|                                   |     |
|-----------------------------------|-----|
| Minimum Tensile Strength (Metric) | 535 |
|-----------------------------------|-----|

|                     |      |
|---------------------|------|
| Length L (Imperial) | 15.0 |
|---------------------|------|

|                   |       |
|-------------------|-------|
| Length L (Metric) | 385.0 |
|-------------------|-------|

|                 |             |
|-----------------|-------------|
| Fixation Method | Screw Mount |
|-----------------|-------------|

|                               |      |
|-------------------------------|------|
| Identification Plate Position | none |
|-------------------------------|------|

|                    |    |
|--------------------|----|
| Releasable Closure | No |
|--------------------|----|

|             |              |
|-------------|--------------|
| Tie Closure | plastic pawl |
|-------------|--------------|

|         |                 |
|---------|-----------------|
| Variant | Inside Serrated |
|---------|-----------------|

|                    |      |
|--------------------|------|
| Width W (Imperial) | 0.30 |
|--------------------|------|

|                  |     |
|------------------|-----|
| Width W (Metric) | 7.6 |
|------------------|-----|

|                                |     |
|--------------------------------|-----|
| Bundle Diameter Min (Imperial) | 0.2 |
|--------------------------------|-----|

|                              |     |
|------------------------------|-----|
| Bundle Diameter Min (Metric) | 5.0 |
|------------------------------|-----|

|                                |      |
|--------------------------------|------|
| Bundle Diameter Max (Imperial) | 4.13 |
|--------------------------------|------|

|                              |       |
|------------------------------|-------|
| Bundle Diameter Max (Metric) | 105.0 |
|------------------------------|-------|

|                                       |                                                                                                                                           |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Thickness T (Imperial)                | 0.07                                                                                                                                      |
| Thickness T (Metric)                  | 1.8                                                                                                                                       |
| Height H (Imperial)                   | 0.92                                                                                                                                      |
| Height H (Metric)                     | 23.5                                                                                                                                      |
| Mounting Hole Diameter D (Imperial)   | 0.33                                                                                                                                      |
| Mounting Hole Diameter D (Metric)     | 8.4 mm                                                                                                                                    |
| Mounting Hole Diameter D Max (Metric) | 8.5                                                                                                                                       |
| Stud Diameter (Metric)                | 8.0 mm                                                                                                                                    |
| Stud Diamater (Imperial)              | 0.31                                                                                                                                      |
| Material                              | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Foot Part Material                    | PA66HIRHSUV                                                                                                                               |
| Material Shortcut                     | PA66HIRHS PA66HIRHSUV                                                                                                                     |
| Material Cable Tie                    | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)                                                                          |
| Flammability                          | UL 94 HB                                                                                                                                  |
| Halogen Free                          | Yes                                                                                                                                       |

|                             |                                   |
|-----------------------------|-----------------------------------|
| UV Resistant (Yes/No)       | No                                |
| Use Conditions              | For Indoor and Outdoor Use        |
| Operating Temperature       | -40°F to +230°F (-40°C to +110°C) |
| ROHS Compliant              | Yes                               |
| Package Quantity (Imperial) | 1000                              |
| Package Quantity (Metric)   | 1000                              |
| Customs Number              | 3926909988                        |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.  
[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)