

Specification Sheet

Part Number: 157-00329

Offset mount allows wire or cable to be attached beside mounting hole instead of directly above it.

Reusable fastener can be extracted from threaded or nonthreaded holes using a 5/16" hex driver.

Delivers high extraction force for reliable performance, yet it's easy to install.

Heat stabilized material provides excellent resistance to high temperatures.



Blind Hole Mount Cable Tie, Offset, 8"L, 0.25" Thread/Non-Thread Hole, 50lb, PA66HS, Black, 500/bg

Article Number

157-00329

Type

T50ROSBHMBSO18

Color

Black (BK)

Quantity Per

bag

Product Description

Blind Hole Mount Offset Cable Ties secure bundles beside the mounting hole instead of directly above it. The unique design includes a heat stabilized cable tie and formula-matched, hex-head fastener that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or non-threaded blind holes. Since cable or wire bundle is beside the fastener, the assembly can be removed using a hex driver from the mounting hole without cutting the cable tie. The fastener can then be reused.

Short Description	Blind Hole Mount Cable Tie, Offset, 8"L, 0.25" Thread/Non-Thread Hole, 50lb, PA66HS, Black, 500/bg
Global Part Name	T50ROSBHMBSO18-PA66HS-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.0
Length L (Metric)	203.2
Offset Length (Imperial)	0.71
Offset Length (Metric)	18.0
Fixation Method	Blind Plug
Identification Plate Position	none
Releasable Closure	No
Width W (Imperial)	0.185
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97

Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.736
Height H (Metric)	18.7
Diameter D (Imperial)	0.25
Diameter D (Metric)	6.35
Mounting Hole Diameter D (Imperial)	0.246 - 0.253
Mounting Hole Diameter D (Metric)	6.25 - 6.45 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.25
Mounting Hole Diameter D Max (Metric)	6.45

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use

Operating Temperature	-40°F to +257°F (-40°C to +125°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)