

## **Specification Sheet**

Part Number: 2N0M



Sheathing allows flexible routing and lead-out of cables

The inner edges are beveled preventing damage to cables

Sheathing is reusable and resistant to most chemicals

Spiralwrap is U.L. Recognized

Spiralwrap Protective Sheathing, 0.25" Diameter, PA6, Black, 1000ft/roll

Article Number 161-05033

Type 2N

Color Black (BK)

Quantity Per reel

| Product Description | HellermannTyton Spiralwrap provides an effective means for routing          |
|---------------------|---|
|                     | and securing wires around corners and bends, and helps keep wires           |
|                     | out of pinch points within moving panel doors. Spiralwrap is installed      |
|                     | using a gapped or butted installation which impacts harnesses               |
|                     | flexibility, wire coverage and abrasion resistance. A gapped installation   |
|                     | leaves space between the sheathing to accommodate breakouts and             |
|                     | adds flexibility to the harness. A butted installation wraps tightly around |
|                     | the bundle to provide greater abrasion resistance and add rigidity.         |
|                     | Natural PA6 nylon material is recommended for use within enclosed           |
|                     | environments where possibility of fire exists. Black PA6 nylon material     |

Short Description Spiralwrap Protective Sheathing, 0.25" Diameter, PA6, Black, 1000ft/roll

extended periods of time.

is suitable for outdoor applications and can be used in direct sunlight for

Global Part Name 2N-PA6-BK

Length L (Imperial) 1000.0

Length L (Metric) 304.8

Variant Spiral Binding

Bundle Diameter Min (Imperial) 0.19

Bundle Diameter Min (Metric) 4.75

Bundle Diameter Max (Imperial) 2

Bundle Diameter Max (Metric) 50.8

Diameter D (Imperial) 0.25

Diameter D (Metric) 5.1

| Nominal Diameter (Imperial)  | 0.25                              |
|------------------------------|-----------------------------------|
| Nominal Diameter (Metric)    | 6.35                              |
| Wall Thickness WT (Imperial) | .025                              |
| Wall Thickness WT (Metric)   | 0.64                              |
|                              |                                   |
|                              |                                   |
| Material                     | Polyamide 6 (PA6)                 |
| Material Shortcut            | PA6                               |
| Flammability                 | UL 94 HB                          |
| UV Resistant (Yes/No)        | No                                |
| Use Conditions               | For Indoor Use Only               |
| Operating Temperature        | -40°F to +250°F (-40°C to +121°C) |
| Reach Compliant (Article 33) | No                                |
| ROHS Compliant               | Yes                               |
|                              |                                   |
| Package Quantity (Imperial)  | 1000                              |
| Package Quantity (Metric)    | 304.8                             |
| Customs Number               | 3926909988                        |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

 $\hbox{@\,}2025$  HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions