

Specification Sheet

Part Number: CTN580STD

Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture.

Tubing protects cables and wires against automotive fluids and vibration wear.

Weather resistant material provides protection against water, snow, ice, and the effects of heat or cold.

Nylon material is formulated to withstand high temperatures.

Lateral slit allows fast and easy insertion of wires.



Convoluted Tubing, Slit, 0.63" Dia, PA6, Black with Gray Stripe, 800 ft/carton

Article Number 169-60017

Type CTN580

Color Black with Gray Stripe (BKSTGY)

Quantity Per carton

Product Description Convoluted tubing provides an efficient method of routing and

protecting wire harness assemblies, while reducing the chance of installation damage. It also can serve to protect valuable wiring circuits. HellermannTyton's convoluted tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat or cold on cables and wires. Available in standard, bulk, and

dispenser box packaging. Material is slit.

Short Description	Convoluted Tubing, Slit, 0.63" Dia, PA6, Black with Gray Stripe, 800 ft/carton
Global Part Name	CTN580-PA6-BK
Length L (Imperial)	800.0
Length L (Metric)	243.8
Variant	Slit
Inner Diameter D (Imperial)	0.639
Inner Diameter D (Metric)	16.23
Diameter D (Imperial)	0.837
Diameter D (Metric)	21.26
Outside Diameter OD (Imperial)	0.837
Outside Diameter OD (Metric)	21.26
Nominal Diameter (Imperial)	0.63
Nominal Diameter (Metric)	16.00
Wall Thickness WT (Imperial)	0.005
Wall Thickness WT (Metric)	0.127

Material Polyamide 6 (PA6)

Material Shortcut PA6

Flammability UL 94 HB

Halogen Free No

UV Resistant (Yes/No) No

Use Conditions For Indoor Use Only

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 800

Package Quantity (Metric) 243.80

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions