

Specification Sheet

Part Number: 169-60109

Tubing provides full coverage where spiral wrap or other coverings may not be suitable.

In harsh applications the tubing provides resistance to crushing, impact, and abrasion.



Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Convoluted Tubing, Flame Retardant, Unslit, 0.50" Dia, PP, Black, 1000 ft/ctn

Article Number 169-60109

Type CTPPFR120UNSLIT

Color Black with Blue Stripe (BKSTBL)

Quantity Per carton

Product Description HellermannTyton's Convoluted Tubing, also known as Loom Tubing,

provides an efficient method of routing and protecting wire harness assemblies while reducing the chance of installation damage. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires. The Polypropylene flame retardant material provides additional protection that is suitable for applications requiring a self-extinguishing material and complies with UL 94 V2 standards.

Short Description	Convoluted Tubing, Flame Retardant, Unslit, 0.50" Dia, PP, Black, 1000 ft/ctn
Global Part Name	CTPPFR120UNSLIT-PPFR-BK
Length L (Imperial)	1000.0
Length L (Metric)	304.8
Variant	Unslit
Inner Diameter D (Imperial)	0.516
Inner Diameter D (Metric)	13.11
Diameter D (Imperial)	0.70
Diameter D (Metric)	17.78
Outside Diameter OD (Imperial)	0.70
Outside Diameter OD (Metric)	17.78
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	12.70
Wall Thickness WT (Imperial)	0.005
Wall Thickness WT (Metric)	0.127

Material Polypropylene, flame retardant (PPFR)

Material Shortcut PPFR

Flammability UL 94 V-2

Halogen Free No

UV Resistant (Yes/No) No

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 304.80

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions