## **HellermannTyton**

## **Specification Sheet**

Part Number: CTP1120



Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.

Tubing provides full coverage where spiral wrap or other coverings may not be suitable.

In harsh applications the tubing provides resistance to crushing, impact, and abrasion.

Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Convoluted Tubing, Slit, 1.5" Dia, PE, Black, 1000 ft/carton

Article Number

Туре

CTP1120

169-60502

Color

Black (BK)

**Quantity Per** 

carton

| Product Description            | HellermannTyton's Convoluted Tubing, also known at Split Loom<br>Tubing, provides an efficient method of routing and protecting wire<br>harness assemblies, while reducing the chance of installation damage.<br>With a split down the side where you can insert your wire harness, you<br>can just easily install Convoluted Tubing without removal of the entire<br>assembly. It can also serve to protect valuable hoses and cables.<br>Convoluted tubing offer's excellent protection against vibration wear,<br>water, snow, ice and the effects of heat, cold and sunlight on cables and<br>wires. |
|--------------------------------|--|
| Short Description              | Convoluted Tubing, Slit, 1.5" Dia, PE, Black, 1000 ft/carton   |
| Global Part Name               | CTP1120-PE-BK  |
|                                |  |
| Length L (Imperial)            | 1000.0   |
| Length L (Metric)              | 304.8  |
| Variant                        | Slit   |
| Inner Diameter D (Imperial)    | 1.647  |
| Inner Diameter D (Metric)      | 41.83  |
| Diameter D (Imperial)          | 1.947  |
| Diameter D (Metric)            | 49.45  |
| Outside Diameter OD (Imperial) | 1.947  |
| Outside Diameter OD (Metric)   | 49.45  |
| Nominal Diameter (Imperial)    | 1.5  |

| Nominal Diameter (Metric)    | 38.1                             |
|------------------------------|----------------------------------|
| Wall Thickness WT (Imperial) | 0.006                            |
| Wall Thickness WT (Metric)   | 0.152                            |
|                              |                                  |
|                              |                                  |
| Material                     | Polyethylene (PE)                |
| Material Shortcut            | PE                               |
| Flammability                 | Not Flame Retardant              |
| Halogen Free                 | No                               |
| UV Resistant (Yes/No)        | No                               |
| Use Conditions               | For Indoor Use Only              |
| Operating Temperature        | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes                              |
| ROHS Compliant               | Yes                              |
|                              |                                  |
| Package Quantity (Imperial)  | 1000                             |
| Package Quantity (Metric)    | 304.80                           |
| Customs Number               | 3926909988                       |

7930 N. Faulkner Road, Milwaukee, WI 53224 Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions