

Specification Sheet

Part Number: CTP20STD



- Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture
- Tubing protects cables and wires against automotive fluids, vibration wear
- Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight

Convoluted Tubing, Slit, 2" Dia, PE, Black, 100 ft/carton

Article Number	169-60511
Type	CTP20
Color	Black (BK)
Quantity Per	carton
Product Description	<p>HellermannTyton’s Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer’s excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.</p>

Short Description	Convuluted Tubing, Slit, 2" Dia, PE, Black, 100 ft/carton
-------------------	---

Global Part Name	CTP20-PE-BK
------------------	-------------

Length L (Imperial)	100.0
---------------------	-------

Length L (Metric)	30.4
-------------------	------

Variant	Slit
---------	------

Inner Diameter D (Imperial)	2.038
-----------------------------	-------

Inner Diameter D (Metric)	51.77
---------------------------	-------

Diameter D (Imperial)	2.388
-----------------------	-------

Diameter D (Metric)	60.66
---------------------	-------

Outside Diameter OD (Imperial)	2.388
--------------------------------	-------

Outside Diameter OD (Metric)	60.66
------------------------------	-------

Nominal Diameter (Imperial)	2
-----------------------------	---

Nominal Diameter (Metric)	50.8
---------------------------	------

Wall Thickness WT (Imperial)	0.011
------------------------------	-------

Wall Thickness WT (Metric)	0.28
----------------------------	------

Material	Polyethylene (PE)
Material Shortcut	PE
Flammability	Not Flame Retardant
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com