HellermannTyton

Specification Sheet

Part Number: 169-60549

Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.

Tubing provides full coverage where spiral wrap or other coverings may not be suitable.



Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Convoluted Tubing, Slit, 0.5" Dia, PE, Orange, 1100 ft/carton

Article Number 169-60549

Type CTP120

Color Orange (OG), High Voltage (HV)

Quantity Per carton

Product Description HellermannTyton's Convoluted Tubing, also known at Split Loom

Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description	Convoluted Tubing, Slit, 0.5" Dia, PE, Orange, 1100 ft/carton
Global Part Name	CTP120-PE-OG
Length L (Imperial)	1100.0
Length L (Metric)	335.3
Variant	Slit
Inner Diameter D (Imperial)	0.516
Inner Diameter D (Metric)	13.11
Diameter D (Imperial)	0.70
Diameter D (Metric)	17.78
Outside Diameter OD (Imperial)	0.70
Outside Diameter OD (Metric)	17.78
Nominal Diameter (Imperial)	1/2
Nominal Diameter (Metric)	12.70
Wall Thickness WT (Imperial)	0.005

0.127

Wall Thickness WT (Metric)

Material Polyethylene (PE)

Material Shortcut PE

Flammability Not Flame Retardant

Halogen Free No

UV Resistant (Yes/No) No

Use Conditions For Indoor Use Only

Operating Temperature -40°F to +185°F (-40°C to +85°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

Package Quantity (Imperial) 1100

Package Quantity (Metric) 335.30

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions