

## **Specification Sheet**

Part Number: 170-03044

Weave construction adjusts to twisting and flexing without creating wrinkles or bends.

Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.

Color options available to provide easy visual and safety identification of critical wiring components.

Expands to 150% of nominal diameter for fast, easy installation.



Braided Sleeving, Expandable, 1" Dia, PET, Black, 250 ft/bulk reel

Article Number 170-03044

Type BSP100B

Color Black (BK)

Quantity Per reel

**Product Description** 

Designed to adjust and expand to irregular shapes, this general purpose sleeving is lightweight and offers a high tensile strength while still maintaining flexibility. This sleeving is an excellent choice for protecting wire and cable bundles from abrasion, chafing and heat degradation. Commonly used in electrial and industrial wire harnessing application where economy and durability are required for the protection of wires, cables, tubing, bundles and pneumatic hoses.

Short Description	Braided Sleeving, Expandable, 1" Dia, PET, Black, 250 ft/bulk reel	
Global Part Name	BSP100B-PET-BK	
Length L (Imperial)	250.0	
Length L (Metric)	76.2	
Bundle Diameter Min (Imperial)	0.63	
Bundle Diameter Min (Metric)	15.9	
Bundle Diameter Max (Imperial)	1.63	
Bundle Diameter Max (Metric)	41.3	
Diameter D (Imperial)	1.0	
Diameter D (Metric)	25.4	
Nominal Diameter (Imperial)	1	
Nominal Diameter (Metric)	25.4	
Material	Polyester (PET)	
Material Shortcut	PET	

Flammability FMVSS 302 FAR 25 UL 94 V-0

Halogen Free	Yes

UV Resistant (Yes/No) No

Use Conditions For Indoor Use Only

Operating Temperature -94°F to +257°F (-70°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

UL Recognized (US) Yes

Package Quantity (Imperial) 250

Package Quantity (Metric) 76.20

Customs Number 5808100000

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions