

Specification Sheet

Part Number: 170-03072



Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.

Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Braided Sleeving, Expandable, Flame Retardant, 0.25" Dia, PET, Gray, 200 ft/reel

|                     |                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 170-03072                                                                                                                                                                                                                                                                                                                                                                                                  |
| Type                | BSPFR148                                                                                                                                                                                                                                                                                                                                                                                                   |
| Color               | Gray (GY)                                                                                                                                                                                                                                                                                                                                                                                                  |
| Quantity Per        | reel                                                                                                                                                                                                                                                                                                                                                                                                       |
| Product Description | A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification. This fire extinguishing braided sleeving is ideal for electronic and high tech applications because of its lightweight and durable qualities. |
| Short Description   | Braided Sleeving, Expandable, Flame Retardant, 0.25" Dia, PET, Gray, 200 ft/reel                                                                                                                                                                                                                                                                                                                           |

|                                |                                      |
|--------------------------------|--------------------------------------|
| Global Part Name               | BSPFR148-PET-GY                      |
| Length L (Imperial)            | 200.0                                |
| Length L (Metric)              | 61.0                                 |
| Bundle Diameter Min (Imperial) | 0.13                                 |
| Bundle Diameter Min (Metric)   | 3.2                                  |
| Bundle Diameter Max (Imperial) | 0.44                                 |
| Bundle Diameter Max (Metric)   | 11.1                                 |
| Diameter D (Imperial)          | 0.25                                 |
| Diameter D (Metric)            | 6.4                                  |
| Nominal Diameter (Imperial)    | 0.25                                 |
| Nominal Diameter (Metric)      | 6.4                                  |
| Material                       | Polyester (PET)                      |
| Material Shortcut              | PET                                  |
| Flammability                   | FAR 25 FMVSS 302 Mil-202 UL 224 VW-1 |
| Halogen Free                   | Yes                                  |

|                              |                                   |
|------------------------------|-----------------------------------|
| UV Resistant (Yes/No)        | No                                |
| Use Conditions               | For Indoor Use Only               |
| Operating Temperature        | -94°F to +257°F (-70°C to +125°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Certification/Specification  | UL 94 VW-1                        |
| UL Recognized (US)           | Yes                               |
| Package Quantity (Imperial)  | 200                               |
| Package Quantity (Metric)    | 60.96                             |
| Customs Number               | 5808100000                        |

7930 N. Faulkner Road, Milwaukee, WI 53224  
 Phone: (800) 537-1512 | Email: corp@htamericas.com