

Specification Sheet

Part Number: 170-03102

Resists gasoline and engine chemicals.

Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

Expands up to 150% for economical and expeditious installation.

Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.

Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.



Plenum Rated Expandable Braided Sleeving (Halar), 0.38" Dia, Black, 125 ft/reel

Article Number 170-03102

Type BSHLR380

Color Black (BK)

Quantity Per reel

Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern. This sleeving is made from strands of high temperature, flame resistant Halar monofilaments that are able to resist a wide range of corrosive chemicals and organic solvents. Its low flame spread and smoke generation properties make it the perfect option for use in technologically advanced applications, such as those in the automotive, aerospace and vital military markets.
Short Description	Plenum Rated Expandable Braided Sleeving (Halar), 0.38" Dia, Black, 125 ft/reel
Global Part Name	BSHLR380-E/CTFE-BK
Length L (Imperial)	125.0
Length L (Metric)	38.1
Bundle Diameter Min (Imperial)	0.19
Bundle Diameter Min (Metric)	4.7
Bundle Diameter Max (Imperial)	0.63
Bundle Diameter Max (Metric)	16.0
Diameter D (Imperial)	0.38
Diameter D (Metric)	9.5
Nominal Diameter (Imperial)	0.38

9.5

Nominal Diameter (Metric)

Material Ethylene Chlorotrifluoroethylene (E/CTFE)

Material Shortcut E/CTFE

Flammability UL VW-1 FAR 25

Halogen Free No

UV Resistant (Yes/No) No

Use Conditions For Indoor and Outdoor Use

Operating Temperature -103°F to +302°F (-75°C to +150°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

Certification/Specification UL | UL 746A UL | ANSI/UL 746B UL | UL 1441 UL 2024

UL Recognized (US) Yes

Package Quantity (Imperial) 125

Package Quantity (Metric) 38.10

Customs Number 5808100000

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions