

Specification Sheet

Part Number: 170-03198



A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.

Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.

Cuts with ordinary scissors for fast, easy application.

Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 2" Dia, AL/GF, Silver, 2/box

|                     |                                                                                                                                                                                                                                                                                                |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 170-03198                                                                                                                                                                                                                                                                                      |
| Type                | BSHTTSW2SB                                                                                                                                                                                                                                                                                     |
| Color               | Silver (SR)                                                                                                                                                                                                                                                                                    |
| Quantity Per        | box                                                                                                                                                                                                                                                                                            |
| Product Description | Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance. Sold in 4-foot sticks. |
| Short Description   | Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, 2" Dia, AL/GF, Silver, 2/box                                                                                                                                                                                                       |

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Global Part Name               | BSHTTSW2SB-GF-AL-SR                     |
| Length L (Imperial)            | 4.0                                     |
| Length L (Metric)              | 1.22                                    |
| Bundle Diameter Min (Imperial) | 0.1                                     |
| Bundle Diameter Min (Metric)   | 2.54                                    |
| Bundle Diameter Max (Imperial) | 1.95                                    |
| Bundle Diameter Max (Metric)   | 49.5                                    |
| Diameter D (Imperial)          | 2.0                                     |
| Diameter D (Metric)            | 50.80                                   |
| Nominal Diameter (Imperial)    | 2                                       |
| Nominal Diameter (Metric)      | 50.8                                    |
| Wall Thickness WT (Imperial)   | 0.042                                   |
| Wall Thickness WT (Metric)     | 1.06                                    |
| Material                       | Glass fiber with aluminium foil (GF-AL) |
| Material Shortcut              | GF-AL                                   |

|                              |                                   |
|------------------------------|-----------------------------------|
| Halogen Free                 | Yes                               |
| UV Resistant (Yes/No)        | No                                |
| Use Conditions               | For Indoor Use Only               |
| Operating Temperature        | -76°F to +491°F (-60°C to +255°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 2                                 |
| Package Quantity (Metric)    | 2                                 |
| Customs Number               | 7019905150                        |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)