

Specification Sheet

Part Number: 181-94007

A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.

Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.



Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

Article Number 181-94007

Type TC4

Color Blue (BU)

Quantity Per carton

Product Description HellermannTyton's Pro-Duct wiring duct covers are sold separately and

interchangeable among the 3 styles of duct (solid, slotted and high density). Manufactured from high impact, rigid PVC, Pro-Duct covers come in standard colors of white, gray and black. Wiring duct covers

are available in 6 foot lengths.

Short Description Wiring Duct Cover for 4" Duct, 6 ft Long, PVC, Intrinsic Blue, 120

ft/carton

Global	Dort	Nomo
GIODAI	ran	manne

TC4-PVC-BU

Length L (Imperial)

6.0

Length L (Metric)

1.83

Width W (Imperial)

4.0

Width W (Metric)

101.6

Height H (Imperial)

0.317

Height H (Metric)

8.05

Material

Polyvinylchloride (PVC)

Material Shortcut

PVC

Flammability

UL 94 V-0

Halogen Free

No

UV Resistant (Yes/No)

No

Operating Temperature

+122°F (+50°C)

Reach Compliant (Article 33)

No

ROHS Compliant

Yes

Certification/Specification	CSA EN 50085-1:2005 + A1:2013 UL EN 50085-2-3_1A
-----------------------------	--

UL Recognized (US) Yes

Package Quantity (Imperial) 120.0

Package Quantity (Metric) 36.58

Customs Number 3925900000

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

 $\hbox{@\,}2025$ HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions