


## Specification Sheet

Part Number: 183-24040



Narrow slots suitable for small-diameter wires.

Fingers can be removed with no sharp edges at pre-notched snap-off points.

Duct covers hold securely even in a vertical position and under vibration.

Base perforation according to DIN EN 50085.

Article Number

183-24040

Type

HTWD-HF-40X40

Color

Gray (GY)

Quantity Per

box

Product Description

HelaDuct HTWD-HF wiring duct is used to route and protect wires in control panels and switching systems where there are high demands on personal or material safety in case of fire, such as in public transport, tunnels, data processing centers or public buildings. Snap-on covers are included with corresponding duct sizes to ensure complete wire protection.

Short Description

Halogen Free Slotted Wiring Duct & Cover, without Adhesive, 40mm x 40mm, Piece/ABS, Gray, 50 m/Box

|                              |                                                                     |
|------------------------------|---------------------------------------------------------------------|
| Global Part Name             | HTWD-HF-40X40-PC/ABS-GY                                             |
| Length L (Imperial)          | 6.56                                                                |
| Length L (Metric)            | 2.0                                                                 |
| Fixation Method              | Screw Mounting                                                      |
| Width W (Imperial)           | 1.58                                                                |
| Width W (Metric)             | 40.0                                                                |
| Height H (Imperial)          | 1.58                                                                |
| Height H (Metric)            | 40.0                                                                |
| Material                     | Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS) |
| Material Shortcut            | PC/ABS                                                              |
| Flammability                 | UL 94 V-0                                                           |
| Halogen Free                 | Yes                                                                 |
| UV Resistant (Yes/No)        | No                                                                  |
| Operating Temperature        | -13°F to +194°F (-25°C to +90°C)                                    |
| Reach Compliant (Article 33) | Yes                                                                 |

|                               |                                                                                                    |
|-------------------------------|----------------------------------------------------------------------------------------------------|
| ROHS Compliant                | Yes                                                                                                |
| Certification/Specification   | UL   ANSI/UL 62275 UL   ANSI/UL 1565 UL   csa-C22.2 no. 62275 UL   csa-C22.2 no. 18.5 EN [45545-2] |
| UL Recognized (US)            | Yes                                                                                                |
| UL Recognized (US and Canada) | Yes                                                                                                |
| Package Quantity (Imperial)   | 164.04                                                                                             |
| Package Quantity (Metric)     | 50.0                                                                                               |
| Customs Number                | 3925900000                                                                                         |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com