

Specification Sheet

Part Number: 184-11005

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 1" x 1", Non-Adhesive, PVC, White, 30ft/Box

Article Number 184-11005

Type SLHD1X1

Color White (WH)

Quantity Per box

Product Description HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct

features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs

and components are more easily accommodated.

| Short Description | High Density Slotted Wall Wiring Duct, 1" x 1", Non-Adhesive, PVC, White, 30ft/Box |
|----------------------------------|--|
| Global Part Name | SLHD1X1-PVC-WH |
| | |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Width W (Imperial) | 1.0 |
| Width W (Metric) | 25.4 |
| Height H (Imperial) | 1.06 |
| Height H (Metric) | 26.9 |
| Mounting Hole Centers (Imperial) | 2.0 |
| | |
| | |
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor Use Only |

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

UL Recognized (US) Yes

Package Quantity (Imperial) 30.0

Package Quantity (Metric) 9.14

Customs Number 3925900000

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions