

Specification Sheet

Part Number: 309-65144

Thin, 2 to 1 shrink ratio tubing provides insulation and abrasion protection for wires and cables.

Flammability rating of UL224 VW-1 for use in applications requiring the highest degree of flame protection (excludes clear tubing).

Flexible-yet-durable material resists most common oils, chemicals and fluids.

Available in a variety of diameters and colors for identifying and marking wires and cables.

Available in mini reels, bulk reels, and sticks for small to large volume applications.



Article Number 309-65144

Type TFN21-ST 6.4/3.2

Color Black (BK)

Quantity Per pcs.

Product Description

TFN21 is a highly flexible thin wall heat shrink tubing with a 2 to 1 shrink ratio and excellent flame retardant properties. In addition to providing insulation and abrasion protection for wires and cables, the polyolefin material also offers resistance to oils, solvents and chemicals. Available in mini reels, bulk reels and sticks, for small to large volume applications.

Short Description	Heat Shrink Tubing, 4' Long Stick, 2:1 Shrink Ratio, 1/4", 6.4/3.2 Dia,
-------------------	---

PO, Black, 15/pkg

Global Part Name TFN21-ST 6.4/3.2-PO-X-BK

Variant Thin-Wall

Nominal Diameter (Imperial) 0.25

Nominal Diameter (Metric) 6.4

Wall Thickness WT (Imperial) .022

Wall Thickness WT (Metric) 0.56

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

Flammability UL 224 VW-1

Halogen Free No

UV Resistant (Yes/No) No

Operating Temperature -67°F to +275°F (-55°C to +135°C)

Reach Compliant (Article 33) Yes

ROHS Compliant	Yes
Certification/Specification	CSA UL ANSI/UL 224
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	15
Package Quantity (Metric)	15
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

 $\hbox{@\,}2025$ HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions