

Specification Sheet

Part Number: 333-41502

Thin wall, flexible 3 to 1 shrink ratio material accommodates a wide range of component shapes and diameters.

Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing).



Polyolefin material provides excellent insulation and mechanical strength with good resistance to solvents, oils and fuels.

Available in bulk reels, sticks and convenience bags (HIS-3 bags), for small to large volume applications.

Heat Shrink Tubing, Bulk Reel, 3:1 Shrink Ratio, 3/8",9.5/3.0 Dia, PO, Black, 500 ft/reel

Article Number 333-41502

Type TFN31 9/3

Color Black (BK)

Quantity Per reel

Product Description

TFN31 series heat shrink tubing features a flexible, thin wall and highly flame retardant polyolefin material with a higher operating temperature range than general-use heat shrink tubing. and offers good resistance to solvents, oils and fuels. The 3 to 1 shrink ratio accommodates a variety of component shapes and sizes. TFN31 tubing is available in bulk reels, sticks and convenience bags (HIS-3 bags), for projects of all sizes.

Short Description	Heat Shrink Tubing, Bulk Reel, 3:1 Shrink Ratio, 3/8",9.5/3.0 Dia, PO, Black, 500 ft/reel
Global Part Name	TFN31 9/3-PO-X-BK
Length L (Imperial)	500.0
Length L (Metric)	152.4
Variant	Thin-Wall
Nominal Diameter (Imperial)	0.38
Nominal Diameter (Metric)	9
Wall Thickness WT (Imperial)	.029
Wall Thickness WT (Metric)	0.75
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
Flammability	UL 224 VW-1
Halogen Free	No

No

UV Resistant (Yes/No)

Use Conditions For Indoor Use Only

Operating Temperature -58°F to +275°F (-50°C to +135°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification CSA | C22.2 no. 198.1-06 UL | ANSI/UL 224

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 152.4

Customs Number 3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions