



Product: [FRCC1YL](#)



Fiber Raceway Cross Connector, 2x2

Product Description

Fiber Raceway Cross Connector, 2x2 (50mm x 50mm)

Technical Specifications

Product Overview

|                      |        |
|----------------------|--------|
| Environmental Space: | Indoor |
|----------------------|--------|

Construction

|         |                      |
|---------|----------------------|
| Weight: | 0.154 lbs            |
| Height: | 2.204 in (55.982 mm) |
| Width:  | 5.039 in             |
| Length: | 5.039 in             |

Product Material

Materials

| Material  |
|---|
| Fire retardant plastic, Halogen free, UL94-VO rated |

Related Part Numbers

Variants

| Item #  | Color  | Length   |
|---------|--------|----------|
| FRCC1YL | Yellow | 5.039 in |

Product Notes

|        |  |
|--------|--|
| Notes: | This connector is used to establish a right-angled intersection between two 50-mm ducts. ie. all 4 arms of the connector are connected to 50mm duct or other components using joiner. Joiners are available separately. NOTE: Care should be taken not to lay more than 30mm depth of pigtails or patch cords in troughing; particularly where they cross each other at right angles. This may occur with this connector |
|--------|--|

History

|                      |   |
|----------------------|---|
| Update and Revision: | Revision Number: 0.29 Revision Date: 11-09-2022 |
|----------------------|---|

© 2023 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.