

## Specification Sheet

Part Number: 556-83013

TAGLF is a limited fire hazard Tiptag that can be used in confined spaces where fire is a concern.

Halogen free so that it will not release toxic fumes if exposed to fire.

TAGLF is a low-smoke, low fire hazard product for use in any confined space where cable identification is critical.

Product Image

Tiptag, Halogen Free, 10mm x 51mm, 4 holes, White, 2000 per roll

Article Number

556-83013

Type

TAGLF10X51-4

Color

White (WH)

Quantity Per

box

Product Description

TAGLF is a Tiptag that is designed for confined spaces, such as rail cars, where a low smoke, low fire hazard marker is required. The TAGLF is Halogen free and will not release harmful fumes when burned.

Short Description

Tiptag, Halogen Free, 10mm x 51mm, 4 holes, White, 2000 per roll

Global Part Name

TAGLF10X51-4-PO-X-WH

Length L (Imperial)

2.0

|                              |                                 |
|------------------------------|---------------------------------|
| Length L (Metric)            | 51.5                            |
| Fixation Method              | Others                          |
| Variant                      | Roller form                     |
| Width W (Imperial)           | 0.39                            |
| Width W (Metric)             | 10.4                            |
| Height H (Imperial)          | 0.39                            |
| Width of Liner (Metric)      | 90.0                            |
| Width of Liner (Imperial)    | 3.50                            |
| Cable Tie Width Max (Metric) | 4.6                             |
|                              |                                 |
| Material                     | Polyolefin, cross-linked (PO-X) |
| Material Shortcut            | PO-X                            |
| Flammability                 | ASTM D635                       |
| Halogen Free                 | Yes                             |
| UV Resistant (Yes/No)        | No                              |
| Use Conditions               | For Indoor Use Only             |

|                              |                                                                                        |
|------------------------------|----------------------------------------------------------------------------------------|
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)                                                      |
| Reach Compliant (Article 33) | Yes                                                                                    |
| ROHS Compliant               | Yes                                                                                    |
| Certification/Specification  | EN [45545-2] MIL-STD-202G Method 215K ASTM E 162 ASTM E 662<br>ASTM 1354 SAE - AS81531 |
| Package Quantity (Imperial)  | 2000                                                                                   |
| Package Quantity (Metric)    | 2000                                                                                   |
| Customs Number               | 3920990000                                                                             |
| Labels per Column            | 1                                                                                      |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com