




Product: [FRD4TYL](#)



Fiber Raceway Slotted Duct 4x8 with Lid

Product Description

Fiber Raceway Duct & Snap On Lid, 4x8, 2 meters long

Technical Specifications

Product Overview

Environmental Space:	Indoor
----------------------	--------

Construction

Weight:	10.78 lbs
Height:	4.527 in (114.986 mm)
Width:	9.251 in
Length:	78.740 in

Product Material

Materials

Material
Fire retardant plastic, Halogen free, UL94-VO rated

Related Part Numbers

Variants

Item #	Color	Length
FRD4TYL	Yellow	78.740 in

Product Notes

Notes:	The 220 mm duct lid is a snap fit onto 220mm straight duct. The lid is quickly and easily fitted and removed from 220mm straight duct, when required. Both the lid and duct are made of tough Noryl plastic with a non - halogen fire retardent. The duct connects to other duct sections and various bends, adapters, etc, using either: a standard joiner or a slotless joiner which are available separately. A 220mm duct carries up to 800 x 3mm dia optical fibre cords to a depth of 50mm, without causing excessive crushing or stress on them. This is the maximum recommended number of optical fibre cords for 220mm duct.
--------	---

History

Update and Revision:	Revision Number: 0.96 Revision Date: 11-09-2022
----------------------	---

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.