

EF EXTRA FLEXIBLE CONDUIT

LFMC SEALTITE® EF EXTRA FLEXIBLE CONDUIT



DESCRIPTION:

- Flexible metal core liquid tight conduit
- Designed for applications where no approvals are required
- Also available in black by special order
- Uses standard liquid tight connectors for easy installation
- Additional Put-ups available

SPECIFICATIONS:

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray or Black
- Temp. range: -4°F to +176°F (-20°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant

APPLICATIONS:

- Applications where no approvals are required

See: www.naed.org www.nema.org
www.anacondasealtite.com



Square-Locked Design
3/8" - 2"



Trade Size (mm)	Item ID	Std. Pkg. (feet)	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)	Packages per Pallet
			Min	Max	Min	Max			
3/8" (12)	39402	100	0.485	0.505	0.690	0.710	2.0	21	48
	39404	800							3
1/2" (16)	39412	100	0.620	0.640	0.820	0.840	2.5	25	48
	39413	1000							3
	39414	500							4
3/4" (21)	39422	100	0.815	0.835	1.030	1.050	3.0	39	32
	39428	500							3
	39429	1000							3
1" (27)	39431	100	1.030	1.055	1.290	1.315	4.0	51	24
	39438	400							3
1-1/4" (35)	39441	50	1.370	1.395	1.635	1.660	4.5	66	24
	39448	250							3
1-1/2" (41)	39451	50	1.575	1.600	1.865	1.900	5.5	104	10
	39454	150							3
2" (53)	39461	50	2.020	2.045	2.340	2.375	7.0	136	10
	39468	100							3

FITTINGS FINDER



IP 66/67 with approved fittings