



## Panduct® F1.5X4WH6 Base Wiring Duct

### F1.5X4WH6

The F1.5X4WH6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scorelines allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 1.5" x 4" (38.1 mm x 101.6 mm) and 6' (1.83 m) long. Cover sold separately. Color White.

### Specifications

Product Type	Base Wiring Duct
Application	Narrow slot/finger design provides more slots to fit the spacing of high-density terminal block applications
Color	White
Cover Part Number	C1.5WH6
Flammability Rating	UL94V-0
Includes	Base Only
Standards Met	RoHS Compliant, UL Recognized, CE Compliant; CSA Approved
Material	PVC
Material Properties	Lead-Free
Mount Method	Mounting Holes
Measurement System	Metric
Wiring Duct Style	Narrow Slot Wiring Duct
Wiring Duct Type	F
Overall Length (ft.)	6
Overall Length (m)	1.8
Overall Width (In.)	1.75
Overall Width (mm)	44.5
Overall Height (In.)	4.1
Overall Height (mm)	104.1
Slot Width (In.)	0.2
Slot Width (mm)	5
Sub Brand	Panduct®
Part Features	Narrow finger and slot design closely matches the spacing of high-density components. Upper and lower scorelines allows easy finger and sidewall section removals. Double restricted slot design for retaining wires, eliminating hassle and saving time

**Packaging Detail**

UPC	07498337540
Std. Pkg. Qty.	6
Std. Pkg. Volume (cf)	0.2107
Std. Ctn. Qty.	60
Std. Ctn. Volume (cf)	2.1073