



Panduct® G1.5X3WH6 Base Wiring Duct

G1.5X3WH6

The G1.5X3WH6 Panduct Lead-Free PVC Wide Slot Wiring Duct feature a wide slot/finger design that provides greater sidewall rigidity and is suitable with a range of wire bundle sizes. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. 1.5" x 3.0" (38.1 mm x 76.2 mm) and 6' (1.8 m) long. Cover sold separately. Color White.

Specifications

Product Type	Base Wiring Duct
Application	Wide slot/finger design provides greater sidewall rigidity and can be used in a wide range of applications
Color	White
Cover Part Number	C1.5WH6
Flammability Rating	UL94V-0
Includes	Base Only
Standards Met	RoHS Compliant, UL Recognized, CE Compliant; CSA Approved
Material	PVC
Material Properties	Lead-Free
Mount Method	Mounting Holes
Measurement System	Metric
Wiring Duct Style	Wide Slot Wiring Duct
Wiring Duct Type	G
Overall Length (ft.)	6
Overall Length (m)	1.8
Overall Width (In.)	1.75
Overall Width (mm)	44.5
Overall Height (In.)	3.12
Overall Height (mm)	79.2
Slot Width (In.)	0.31
Slot Width (mm)	7.9
Sub Brand	Panduct®
Part Features	Wide finger and slot design provides greater rigidity and allows use with a wide range of wire and bundle sizes. Upper and lower scorelines allows easy finger and sidewall section removals.

Packaging Detail

UPC	07498354619
Std. Pkg. Qty.	6
Std. Pkg. Volume (cf)	0.1489
Std. Ctn. Qty.	120
Std. Ctn. Volume (cf)	2.9786