



Dry-Shrink™ HSTTV50-T Heat Shrink

HSTTV50-T

Thin wall VW-1 heat shrink on bulk reel, .50" (12.7mm) diameter, black cross-linked polyolefin.

Specifications

Product Type	Heat Shrink Tubing
Adhesive Lined	No
Color	Black
Material	Cross-Linked Polyolefin
Maximum Operating Temperature (°C)	135
Maximum Operating Temperature (°F)	275
Minimum Operating Temperature (°C)	-55
Minimum Operating Temperature (°F)	-67
Nominal Diameter (In.)	0.5
Nominal Diameter (mm)	12.7
Nominal Recovered Wall Thickness (In.)	0.025
Nominal Recovered Wall Thickness (mm)	0.6
Sub Brand	Dry-Shrink™
Overall Length (In.)	2400
Overall Length (ft.)	200
Overall Length (m)	61.1
Overall Length (mm)	60960
Resistance Properties	Flame-Retardant
Standards Met	UL Recognized, CSA Approved, MIL SPEC
Shrink Ratio	2:1
Shrink Temperature (°C)	90
Shrink Temperature (°F)	194
Maximum Recovered Inside Diameter (In.)	0.25
Maximum Recovered Inside Diameter (mm)	6.4
Minimum Expanded Inside Diameter (In.)	0.5
Minimum Expanded Inside Diameter (mm)	12.7
Application	For Dry Locations

Packaging Detail

UPC	07498390678
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.3661
Std. Ctn. Qty.	2
Std. Ctn. Volume (cf)	0.7322