



Product: [FRCB3YL9DK](#)



Fiber Raceway Break-Out, 4x4, Kit

Product Description

Fiber Raceway Break-Out Kit, 4x4 With Lid, 90 Degree Bend Down

Technical Specifications

Product Overview

|                      |        |
|----------------------|--------|
| Environmental Space: | Indoor |
|----------------------|--------|

Construction

|         |                       |
|---------|-----------------------|
| Weight: | 0.943 lbs             |
| Height: | 6.692 in (169.977 mm) |
| Width:  | 10.236 in             |
| Length: | 8.070 in              |

Product Material

Materials

| Material  |
|---|
| Fire retardant plastic, Halogen free, UL94 VO rated |

Related Part Numbers

Variants

| Item #     | Color  | Length   |
|------------|--------|----------|
| FRCB3YL9DK | Yellow | 8.070 in |

Product Notes

|        |   |
|--------|---|
| Notes: | The 90-degree down elbow kit is a 100mm vertical drop off with an external lid, fitted with an outlet guide, using a standard 100mm duct joiner. This outlet guide (eg. an outlet trumpet) enables optical fibre cords to be dropped-off to a lower duct, at a controlled radius of 30mm. It has removable lids that allow quick and easy installation of optical fibre cords within the elbow. This is usually installed where optical fibre cords are to be dropped off below. There is one 100mm outlet to connect to other duct items, using either: a standard joiner or a slotless joiner; that are available separately. |
|--------|---|

History

|                      |   |
|----------------------|---|
| Update and Revision: | Revision Number: 0.29 Revision Date: 11-09-2022 |
|----------------------|---|

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.