



Product: [FRAE1YB](#)



Fiber Raceway End Cap, 2x2, with 2x Snap-Out for Tube

Product Description

Fiber Raceway End Cap, 2x2, with Snap-Out for Tube, Yellow

Technical Specifications

Product Overview

|                      |        |
|----------------------|--------|
| Environmental Space: | Indoor |
|----------------------|--------|

Construction

|         |                      |
|---------|----------------------|
| Weight: | 0.055 lbs            |
| Height: | 1.850 in (46.990 mm) |
| Width:  | 0.551 in             |
| Length: | 2.362 in             |

Product Material

Materials

| Material                                            |
|-----------------------------------------------------|
| Fire retardant plastic, Halogen free, UL94-VO rated |

Related Part Numbers

Variants

| Item #  | Color  | Length   |
|---------|--------|----------|
| FRAE1YB | Yellow | 2.362 in |

Product Notes

|        |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes: | The duct end cover is provided with a 38mm dia knock out tab that allows fitting of a convoluted, flexible tube 32mm ID/38mm OD. This convoluted tube allows optical fibre cords to be dropped off from the duct to lower transmission equipment. The end cover is also used for sealing the open end of a standard 50mm straight duct. It snaps simply into the duct slots and can be removed with a screwdriver should the system need extending. |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

History

|                      |                                                 |
|----------------------|-------------------------------------------------|
| Update and Revision: | Revision Number: 0.29 Revision Date: 11-09-2022 |
|----------------------|-------------------------------------------------|

© 2023 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.