

Features

- Low V_{CE(sat)}
- h_{FE} characterized up to 1A for high current gain hold up
- For general amplification



SOT-23

Absolute Maximum Ratings (T_A=25°C unless otherwise noted)

| Parameter | Symbol | Rating | Unit |
|---|------------------|-------------|------|
| Collector - Base Voltage | V _{CBO} | 170 | V |
| Collector - Emitter Voltage | V _{CEO} | 150 | V |
| Emitter - Base Voltage | V _{EBO} | 5 | V |
| Collector Current - Continuous | I _C | 1 | A |
| Collector Power Dissipation | P _C | 250 | mW |
| Thermal Resistance from Junction to Ambient | R _{θJA} | 500 | °C/W |
| Junction Temperature | T _J | -55 to +150 | °C |
| Storage Temperature | T _{STG} | -55 to +150 | °C |

Electrical Characteristics (T_A=25°C unless otherwise noted)

| Parameter | Symbol | Conditions | Min. | Max. | Unit |
|---|-----------------------|---|------|------|------|
| Collector-Base Breakdown Voltage | V _{(BR)CBO} | I _C =100uA, I _E =0 | 170 | - | V |
| Collector-Emitter Breakdown Voltage ¹ | V _{(BR)CEO} | I _C =10mA, I _B =0 | 150 | - | V |
| Emitter-Base Breakdown Voltage | V _{(BR)EBO} | I _E =100uA, I _C =0 | 5 | - | V |
| Collector Cut-off Current | I _{CBO} | V _{CB} =150V, I _E =0 | - | 0.1 | uA |
| Collector Cut-off Current | I _{CES} | V _{CB} =150V, V _{BE} =0 | - | 0.1 | uA |
| Emitter Cut-off Current | I _{EBO} | V _{EB} =4V, I _C =0 | - | 0.1 | uA |
| DC Current Gain ¹ | h _{FE1} | V _{CE} =10V, I _C =1mA | 100 | - | - |
| | h _{FE2} | V _{CE} =10V, I _C =250mA | 100 | 300 | - |
| | h _{FE3} | V _{CE} =10V, I _C =500mA | 50 | - | - |
| | h _{FE4} | V _{CE} =10V, I _C =1A | 10 | - | - |
| Collector-Emitter Saturation Voltage ¹ | V _{CE(sat)1} | I _C =250mA, I _B =25mA | - | 0.2 | V |
| | V _{CE(sat)2} | I _C =500mA, I _B =50mA | - | 0.3 | |
| Base-Emitter Turn-On Voltage ¹ | V _{BE(on)} | V _{CE} =10V, I _C =500mA | - | 1 | V |
| Base-Emitter Saturation Voltage ¹ | V _{BE(sat)} | I _C =500mA, I _B =50mA | - | 1 | V |
| Transition Frequency | f _T | V _{CE} =10V, I _C =50mA, F=100MHz | 100 | - | MHz |
| Output Capacitance | C _{ob} | V _{CB} =10V, I _E =0, F=1MHz | - | 10 | pF |

Note:

1. Pulse test: pulse width ≤ 300us, duty cycle ≤ 2%.

Typical Electrical and Thermal Characteristic Curves




Figure 1. Collector Current vs. Collector - Emitter Voltage




Figure 2. DC Current Gain vs Collector Current




Figure 3. Base-Emitter Saturation Voltage vs. Collector Current




Figure 4. Collector-Emitter Saturation Voltage vs. Collector Current




Figure 5. Collector Current vs. Base - Emitter Voltage




Figure 6. Power Dissipation vs Ambient Temperature

Typical Electrical and Thermal Characteristic Curves






Figure 7. Capacitance Characteristics

Package Outline Dimensions (SOT-23)



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|-------|----------------------|-------|
| | Min | Max | Min | Max |
| A | 0.900 | 1.150 | 0.035 | 0.045 |
| A1 | 0.000 | 0.100 | 0.000 | 0.004 |
| A2 | 0.900 | 1.050 | 0.035 | 0.041 |
| b | 0.300 | 0.500 | 0.012 | 0.020 |
| c | 0.080 | 0.150 | 0.003 | 0.006 |
| D | 2.800 | 3.000 | 0.110 | 0.118 |
| E | 1.200 | 1.400 | 0.047 | 0.055 |
| E1 | 2.250 | 2.550 | 0.089 | 0.100 |
| e | 0.950 TYP | | 0.037 TYP | |
| e1 | 1.800 | 2.000 | 0.071 | 0.079 |
| L | 0.550 REF | | 0.022 REF | |
| L1 | 0.300 | 0.500 | 0.012 | 0.020 |
| θ | 0° | 8° | 0° | 8° |

Recommended Pad Layout



Note:

1. Controlling dimensions: in millimeters.
2. General tolerance: ±0.05mm.
3. The pad layout is for reference purposes only.

Order Information

| Device | Package | Marking | Quantity | HSF Status |
|---------|---------|---------|-----------------|----------------|
| MMBT495 | SOT-23 | 495 | 3,000pcs / Reel | RoHS Compliant |