


# NPN General Purpose Amplifier

## BCP54


This device is designed for general purpose medium power amplifiers and switching circuits requiring collector currents to 1.2 A. Sourced from Process 38.



1: Base  
2, 4: Collector  
3: Emitter

SOT-223  
CASE 318H

### MARKING DIAGRAM



A = Assembly Location  
Y = Year  
W = Work Week  
BCP54 = Specific Device Code  
■ = Pb-Free Package

(Note: Microdot may be in either location)

### ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted.)

| Symbol         | Parameter  | Ratings     | Unit             |
|----------------|--|-------------|------------------|
| $V_{CEO}$      | Collector-Emitter Voltage                        | 45          | V                |
| $V_{CBO}$      | Collector-Base Voltage                           | 45          | V                |
| $V_{EBO}$      | Emitter-Base Voltage                             | 5.0         | V                |
| $I_C$          | Collector Current – Continuous                   | 1.5         | A                |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range | -55 to +150 | $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

- These ratings are based on a maximum junction temperature of  $150^\circ\text{C}$ .
- These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

### THERMAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted.)

| Symbol          | Characteristic  | Max       | Unit                      |
|-----------------|---|-----------|---------------------------|
| $P_D$           | Total Device Dissipation<br>Derate Above $25^\circ\text{C}$ | 1.5<br>12 | W<br>mW/ $^\circ\text{C}$ |
| $R_{\theta JA}$ | Thermal Resistance,<br>Junction to Ambient                  | 83.3      | $^\circ\text{C}/\text{W}$ |

### ORDERING INFORMATION

| Device | Package              | Shipping               |
|--------|----------------------|------------------------|
| BCP54  | SOT-223<br>(Pb-Free) | 4,000 /<br>Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, [BRD8011/D](http://www.onsemi.com/BRD8011/D).

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted.)

| Symbol | Parameter | Conditions | Min | Max | Unit |
|--------|-----------|------------|-----|-----|------|
|--------|-----------|------------|-----|-----|------|

#### OFF CHARACTERISTICS

|               |                                     |   |        |           |                     |
|---------------|-------------------------------------|---|--------|-----------|---------------------|
| $V_{(BR)CEO}$ | Collector-Emitter Breakdown Voltage | $I_C = 10\text{ mA}, I_B = 0$   | 45     | –         | V                   |
| $V_{(BR)CBO}$ | Collector-Base Breakdown Voltage    | $I_C = 100\text{ }\mu\text{A}, I_E = 0$   | 45     | –         | V                   |
| $V_{(BR)EBO}$ | Emitter-Base Breakdown Voltage      | $I_E = 10\text{ }\mu\text{A}, I_C = 0$  | 5.0    | –         | V                   |
| $I_{CBO}$     | Collector-Cutoff Current            | $V_{CB} = 30\text{ V}, I_E = 0$<br>$V_{CB} = 30\text{ V}, I_E = 0, T_A = 125^\circ\text{C}$ | –<br>– | 100<br>10 | nA<br>$\mu\text{A}$ |
| $I_{EBO}$     | Emitter-Cutoff Current              | $V_{EB} = 5.0\text{ V}, I_C = 0$  | –      | 10        | $\mu\text{A}$       |

#### ON CHARACTERISTICS

|               |                                      |  |    |     |   |
|---------------|--------------------------------------|--|----|-----|---|
| $h_{FE}$      | DC Current Gain                      | $I_C = 5.0\text{ mA}, V_{CE} = 2.0\text{ V}$ | 25 | –   |   |
|               |                                      | $I_C = 150\text{ mA}, V_{CE} = 2.0\text{ V}$ | 40 | 250 |   |
|               |                                      | $I_C = 500\text{ mA}, V_{CE} = 2.0\text{ V}$ | 25 | –   |   |
| $V_{CE(sat)}$ | Collector-Emitter Saturation Voltage | $I_C = 500\text{ mA}, I_B = 50\text{ mA}$    | –  | 0.5 | V |
| $V_{BE(on)}$  | Base-Emitter On Voltage              | $I_C = 500\text{ mA}, V_{CE} = 2.0\text{ V}$ | –  | 1.0 | V |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

## TYPICAL CHARACTERISTICS




Figure 1. Typical Pulsed Current Gain vs Collector Current




Figure 2. Collector-Emitter Saturation Voltage vs Collector Current




Figure 3. Base-Emitter Saturation Voltage vs Collector Current




Figure 4. Base-Emitter ON Voltage vs Collector Current




Figure 5. Collector-Cutoff Current vs Ambient Temperature




Figure 6. Collector-Base Capacitance vs Collector-Base Voltage

## TYPICAL CHARACTERISTICS (Continued)




Figure 7. Gain Bandwidth Product vs Collector Current





Figure 8. Power Dissipation vs Ambient Temperature




SCALE 2:1

**SOT-223**  
**CASE 318H**  
**ISSUE B**


DATE 13 MAY 2020

## NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSIONS D & E1 ARE DETERMINED AT DATUM H. DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. SHALL NOT EXCEED 0.23mm PER SIDE.
4. LEAD DIMENSIONS b AND b1 DO NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION IS 0.08mm PER SIDE.
5. DATUMS A AND B ARE DETERMINED AT DATUM H.
6. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE BODY.
7. POSITIONAL TOLERANCE APPLIES TO DIMENSIONS b AND b1.




| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | ---         | ---  | 1.80 |
| A1  | 0.02        | 0.06 | 0.11 |
| b   | 0.60        | 0.74 | 0.88 |
| b1  | 2.90        | 3.00 | 3.10 |
| c   | 0.24        | ---  | 0.35 |
| D   | 6.30        | 6.50 | 6.70 |
| E   | 6.70        | 7.00 | 7.30 |
| E1  | 3.30        | 3.50 | 3.70 |
| e   | 2.30 BSC    |      |      |
| L   | 0.25        | ---  | ---  |
| ⌀   | 0°          | ---  | 10°  |

**GENERIC MARKING DIAGRAM\***


A = Assembly Location  
Y = Year  
W = Work Week  
XXXXX = Specific Device Code  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.


**RECOMMENDED MOUNTING FOOTPRINT**

\* For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERM/D.

|                         |                    |  |
|-------------------------|--------------------|--|
| <b>DOCUMENT NUMBER:</b> | <b>98ASH70634A</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOT-223</b>     | <b>PAGE 1 OF 1</b>   |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)