

# NXH80T120L2Q0S1G

## T-Type NPC Power Module

1200 V, 55 A IGBT, 600 V, 50 A IGBT

The NXH80T120L2Q0S1G is a power module containing a T-type neutral point clamped (NPC) three level inverter consisting of two 55 A/1200 V half-bridge IGBTs with 40 A/1200 V half-bridge diodes and two 50 A/600 V NP IGBTs with two 50 A/600 V NP diodes. The module also contains an on-board thermistor.

### Features

- T-type NPC Module with 55 A/1200 V and 50 A/600 V IGBTs
- HB IGBT Specifications:  $V_{CE(SAT)} = 2.5$  V,  $E_{SW} = 1000 \mu J$
- NP IGBT Specifications:  $V_{CE(SAT)} = 1.5$  V,  $E_{SW} = 880 \mu J$
- Solder Pins
- Thermistor

### Typical Applications

- Solar Inverter
- Uninterruptible Power Supplies





Figure 1. NXH80T120L2Q0S1G Schematic Diagram




ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)




Q0PACK  
CASE 180AH

### MARKING DIAGRAM



NXH80T120L2Q0S1G = Device Code  
YYWW = Year and Work Week Code  
A = Assembly Site Code  
T = Test Site Code  
G = Pb-Free Package

### PIN CONNECTIONS



### ORDERING INFORMATION

See detailed ordering and shipping information in the dimensions section on page 11 of this data sheet.

# NXH80T120L2Q0S1G

**Table 1. ABSOLUTE MAXIMUM RATINGS** (Note 1)  $T_J = 25^\circ\text{C}$  unless otherwise noted

Rating	Symbol	Value	Unit
<b>HALF BRIDGE IGBT</b>			
Collector-Emitter Voltage	$V_{CES}$	1200	V
Gate-Emitter Voltage	$V_{GE}$	$\pm 20$	V
Continuous Collector Current @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )	$I_C$	57	A
Pulsed Collector Current ( $T_J = 175^\circ\text{C}$ )	$I_{Cpulse}$	171	A
Maximum Power Dissipation @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )	$P_{tot}$	125	W
Short Circuit Withstand Time @ $V_{GE} = 15$ V, $V_{CE} = 600$ V, $T_J \leq 150^\circ\text{C}$	$T_{sc}$	5	$\mu\text{s}$
Minimum Operating Junction Temperature	$T_{JMIN}$	-40	$^\circ\text{C}$
Maximum Operating Junction Temperature	$T_{JMAX}$	150	$^\circ\text{C}$
<b>NEUTRAL POINT IGBT</b>			
Collector-Emitter Voltage	$V_{CES}$	600	V
Gate-Emitter Voltage	$V_{GE}$	$\pm 20$	V
Continuous Collector Current @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )	$I_C$	52	A
Pulsed Collector Current ( $T_J = 175^\circ\text{C}$ )	$I_{Cpulse}$	156	A
Maximum Power Dissipation @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )	$P_{tot}$	95	W
Short Circuit Withstand Time @ $V_{GE} = 15$ V, $V_{CE} = 400$ V, $T_J \leq 150^\circ\text{C}$	$T_{sc}$	5	$\mu\text{s}$
Minimum Operating Junction Temperature	$T_{JMIN}$	-40	$^\circ\text{C}$
Maximum Operating Junction Temperature	$T_{JMAX}$	150	$^\circ\text{C}$
<b>HALF BRIDGE DIODE</b>			
Peak Repetitive Reverse Voltage	$V_{RRM}$	1200	V
Continuous Forward Current @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )	$I_F$	25	A
Repetitive Peak Forward Current ( $T_J = 175^\circ\text{C}$ , $t_p$ limited by $T_{Jmax}$ )	$I_{FRM}$	70	A
Maximum Power Dissipation @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )	$P_{tot}$	54	W
Minimum Operating Junction Temperature	$T_{JMIN}$	-40	$^\circ\text{C}$
Maximum Operating Junction Temperature	$T_{JMAX}$	150	$^\circ\text{C}$
<b>NEUTRAL POINT DIODE</b>			
Peak Repetitive Reverse Voltage	$V_{RRM}$	600	V
Continuous Forward Current @ $T_h = 80^\circ\text{C}$ . ( $T_J = 175^\circ\text{C}$ )	$I_F$	31	A
Repetitive Peak Forward Current ( $T_J = 175^\circ\text{C}$ , $t_p$ limited by $T_{Jmax}$ )	$I_{FRM}$	85	A
Maximum Power Dissipation @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )	$P_{tot}$	53	W
Minimum Operating Junction Temperature	$T_{JMIN}$	-40	$^\circ\text{C}$
Maximum Operating Junction Temperature	$T_{JMAX}$	150	$^\circ\text{C}$
<b>THERMAL PROPERTIES</b>			
Storage Temperature range	$T_{stg}$	-40 to 125	$^\circ\text{C}$
<b>INSULATION PROPERTIES</b>			
Isolation test voltage, $t = 1$ sec, 60 Hz	$V_{is}$	3000	$V_{RMS}$
Creepage distance		12.7	mm

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS, RECOMMENDED OPERATING RANGES and/or APPLICATION INFORMATION for Safe Operating parameters.

**Table 2. RECOMMENDED OPERATING RANGES**

Rating	Symbol	Min	Max	Unit
Module Operating Junction Temperature	$T_J$	-40	( $T_{Jmax}-25$ )	$^\circ\text{C}$

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

# NXH80T120L2Q0S1G

**Table 3. ELECTRICAL CHARACTERISTICS** ( $T_J = 25^\circ\text{C}$  unless otherwise noted)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
<b>HALF BRIDGE IGBT CHARACTERISTICS</b>						
Collector–Emitter Cutoff Current	$V_{GE} = 0 \text{ V}, V_{CE} = 1200 \text{ V}$	$I_{CES}$	—	—	300	$\mu\text{A}$
Collector–Emitter Saturation Voltage	$V_{GE} = 15 \text{ V}, I_C = 80 \text{ A}, T_J = 25^\circ\text{C}$	$V_{CE(\text{sat})}$	—	2.50	2.85	$\text{V}$
	$V_{GE} = 15 \text{ V}, I_C = 80 \text{ A}, T_J = 150^\circ\text{C}$		—	2.15	—	
Gate–Emitter Threshold Voltage	$V_{GE} = V_{CE}, I_C = 1.5 \text{ mA}$	$V_{GE(\text{TH})}$	—	5.45	6.4	$\text{V}$
Gate Leakage Current	$V_{GE} = 20 \text{ V}, V_{CE} = 0 \text{ V}$	$I_{GES}$	—	—	300	$\text{nA}$
Turn-on Delay Time	$T_J = 25^\circ\text{C}$ $V_{CE} = 350 \text{ V}, I_C = 40 \text{ A}$ $V_{GE} = \pm 15 \text{ V}, R_G = 4 \Omega$	$t_{d(\text{on})}$	—	37	—	$\text{ns}$
Rise Time		$t_r$	—	23	—	
Turn-off Delay Time		$t_{d(\text{off})}$	—	190	—	
Fall Time		$t_f$	—	30	—	
Turn-on Switching Loss per Pulse		$E_{\text{on}}$	—	320	—	$\mu\text{J}$
Turn-off Switching Loss per Pulse		$E_{\text{off}}$	—	680	—	
Turn-on Delay Time	$T_J = 125^\circ\text{C}$ $V_{CE} = 350 \text{ V}, I_C = 40 \text{ A}$ $V_{GE} = \pm 15 \text{ V}, R_G = 4 \Omega$	$t_{d(\text{on})}$	—	30	—	$\text{ns}$
Rise Time		$t_r$	—	25	—	
Turn-off Delay Time		$t_{d(\text{off})}$	—	230	—	
Fall Time		$t_f$	—	90	—	
Turn-on Switching Loss per Pulse		$E_{\text{on}}$	—	500	—	$\mu\text{J}$
Turn-off Switching Loss per Pulse		$E_{\text{off}}$	—	1300	—	
Input Capacitance	$V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}, f = 10 \text{ kHz}$	$C_{\text{ies}}$	—	19400	—	$\text{pF}$
Output Capacitance		$C_{\text{oes}}$	—	400	—	
Reverse Transfer Capacitance		$C_{\text{res}}$	—	340	—	
Total Gate Charge	$V_{CE} = 600 \text{ V}, I_C = 80 \text{ A}, V_{GE} = 15 \text{ V}$	$Q_g$	—	800	—	$\text{nC}$
Thermal Resistance – chip-to-heatsink	Thermal grease, Thickness = 100 $\mu\text{m}$ , $\lambda = 0.84 \text{ W/mK}$	$R_{\text{thJH}}$	—	0.76	—	$^\circ\text{C/W}$

## NEUTRAL POINT DIODE CHARACTERISTICS

Diode Forward Voltage	$I_F = 50 \text{ A}, T_J = 25^\circ\text{C}$	$V_F$	—	2.60	2.85	$\text{V}$
	$I_F = 50 \text{ A}, T_J = 150^\circ\text{C}$		—	2.0	—	
Reverse Recovery Time	$T_J = 25^\circ\text{C}$ $V_{CE} = 350 \text{ V}, I_C = 40 \text{ A}$ $V_{GE} = \pm 15 \text{ V}, R_G = 4 \Omega$	$t_{rr}$	—	30	—	$\text{ns}$
Reverse Recovery Charge		$Q_{rr}$	—	305	—	$\mu\text{C}$
Peak Reverse Recovery Current		$I_{RRM}$	—	22	—	$\text{A}$
Peak Rate of Fall of Recovery Current		$di/dt$	—	1870	—	$\text{A}/\mu\text{s}$
Reverse Recovery Energy		$E_{rr}$	—	77	—	$\mu\text{J}$
Reverse Recovery Time		$t_{rr}$	—	34	—	$\text{ns}$
Reverse Recovery Charge	$T_J = 125^\circ\text{C}$ $V_{CE} = 350 \text{ V}, I_C = 40 \text{ A}$ $V_{GE} = \pm 15 \text{ V}, R_G = 4 \Omega$	$Q_{rr}$	—	910	—	$\text{nC}$
Peak Reverse Recovery Current		$I_{RRM}$	—	50	—	$\text{A}$
Peak Rate of Fall of Recovery Current		$di/dt$	—	4200	—	$\text{A}/\mu\text{s}$
Reverse Recovery Energy		$E_{rr}$	—	200	—	$\mu\text{J}$
Thermal Resistance – chip-to-heatsink	Thermal grease, Thickness = 100 $\mu\text{m}$ , $\lambda = 0.84 \text{ W/mK}$	$R_{\text{thJH}}$	—	1.80	—	$^\circ\text{C/W}$

## NEUTRAL POINT IGBT CHARACTERISTICS

Collector–Emitter Cutoff Current	$V_{GE} = 0 \text{ V}, V_{CE} = 600 \text{ V}$	$I_{CES}$	—	—	200	$\mu\text{A}$
Collector–Emitter Saturation Voltage	$V_{GE} = 15 \text{ V}, I_C = 50 \text{ A}, T_J = 25^\circ\text{C}$	$V_{CE(\text{sat})}$	—	1.50	1.75	$\text{V}$
	$V_{GE} = 15 \text{ V}, I_C = 50 \text{ A}, T_J = 150^\circ\text{C}$		—	1.60	—	
Gate–Emitter Threshold Voltage	$V_{GE} = V_{CE}, I_C = 1.2 \text{ mA}$	$V_{GE(\text{TH})}$	—	5.45	6.4	$\text{V}$
Gate Leakage Current	$V_{GE} = 20 \text{ V}, V_{CE} = 0 \text{ V}$	$I_{GES}$	—	—	200	$\text{nA}$

# NXH80T120L2Q0S1G

**Table 3. ELECTRICAL CHARACTERISTICS** ( $T_J = 25^\circ\text{C}$  unless otherwise noted)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
<b>NEUTRAL POINT IGBT CHARACTERISTICS</b>						
Turn-on Delay Time	$T_J = 25^\circ\text{C}$ $V_{CE} = 350 \text{ V}, I_C = 40 \text{ A}$ $V_{GE} = \pm 15 \text{ V}, R_G = 4 \Omega$	$t_{d(on)}$	—	23	—	ns
Rise Time		$t_r$	—	17	—	
Turn-off Delay Time		$t_{d(off)}$	—	108	—	
Fall Time		$t_f$	—	31	—	
Turn-on Switching Loss per Pulse		$E_{on}$	—	360	—	$\mu\text{J}$
Turn-off Switching Loss per Pulse		$E_{off}$	—	520	—	
Turn-on Delay Time	$T_J = 125^\circ\text{C}$ $V_{CE} = 350 \text{ V}, I_C = 40 \text{ A}$ $V_{GE} = \pm 15 \text{ V}, R_G = 4 \Omega$	$t_{d(on)}$	—	27	—	ns
Rise Time		$t_r$	—	17	—	
Turn-off Delay Time		$t_{d(off)}$	—	130	—	
Fall Time		$t_f$	—	75	—	
Turn-on Switching Loss per Pulse		$E_{on}$	—	535	—	$\mu\text{J}$
Turn-off Switching Loss per Pulse		$E_{off}$	—	865	—	
Input Capacitance	$V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}, f = 10 \text{ kHz}$	$C_{ies}$	—	9400	—	$\text{pF}$
Output Capacitance		$C_{oes}$	—	280	—	
Reverse Transfer Capacitance		$C_{res}$	—	250	—	
Total Gate Charge	$V_{CE} = 480 \text{ V}, I_C = 50 \text{ A}, V_{GE} = 15 \text{ V}$	$Q_g$	—	395	—	$\text{nC}$
Thermal Resistance – chip-to-heatsink	Thermal grease, Thickness < 100 $\mu\text{m}$ , $\lambda = 0.84 \text{ W/mK}$	$R_{thJH}$	—	1.00	—	$^\circ\text{C/W}$

## HALF BRIDGE DIODE CHARACTERISTICS


Diode Forward Voltage	$I_F = 40 \text{ A}, T_J = 25^\circ\text{C}$	$V_F$	—	2.65	3.45	V
	$I_F = 40 \text{ A}, T_J = 150^\circ\text{C}$		—	2.15	—	
Reverse Recovery Time	$T_J = 25^\circ\text{C}$ $V_{CE} = 350 \text{ V}, I_C = 40 \text{ A}$ $V_{GE} = \pm 15 \text{ V}, R_G = 4 \Omega$	$t_{rr}$	—	38	—	ns
Reverse Recovery Charge		$Q_{rr}$	—	853	—	$\text{nC}$
Peak Reverse Recovery Current		$I_{RRM}$	—	43	—	A
Peak Rate of Fall of Recovery Current		$di/dt$	—	2600	—	$\text{A}/\mu\text{s}$
Reverse Recovery Energy		$E_{rr}$	—	200	—	$\mu\text{J}$
Reverse Recovery Time		$t_{rr}$	—	300	—	ns
Reverse Recovery Charge	$T_J = 125^\circ\text{C}$ $V_{CE} = 350 \text{ V}, I_C = 40 \text{ A}$ $V_{GE} = \pm 15 \text{ V}, R_G = 4 \Omega$	$Q_{rr}$	—	2550	—	$\text{nC}$
Peak Reverse Recovery Current		$I_{RRM}$	—	57	—	A
Peak Rate of Fall of Recovery Current		$di/dt$	—	2340	—	$\text{A}/\mu\text{s}$
Reverse Recovery Energy		$E_{rr}$	—	390	—	$\mu\text{J}$
Thermal Resistance – chip-to-heatsink	Thermal grease, Thickness < 100 $\mu\text{m}$ , $\lambda = 0.84 \text{ W/mK}$	$R_{thJH}$	—	1.76	—	$^\circ\text{C/W}$

## THERMISTOR CHARACTERISTICS


Nominal resistance		$R_{25}$	—	22	—	$\text{k}\Omega$
Nominal resistance	$T = 100^\circ\text{C}$	$R_{100}$	—	1486	—	$\Omega$
Deviation of $R_{25}$		$\Delta R/R$	-5		5	%
Power dissipation		$P_D$	—	200	—	$\text{mW}$
Power dissipation constant			—	2	—	$\text{mW/K}$
B-value	B(25/50), tolerance $\pm 3\%$		—	3950	—	K
B-value	B(25/100), tolerance $\pm 3\%$		—	3998	—	K

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


**TYPICAL CHARACTERISTICS – Half Bridge IGBT and Neutral Point Diode**




**Figure 1. IGBT Typical Output Characteristics**




**Figure 2. IGBT Typical Output Characteristics**




**Figure 3. IGBT Typical Transfer Characteristics**



**Figure 4. Diode Forward Characteristics**



**Figure 5. Typical Turn On Loss vs. IC**



**Figure 6. Typical Turn Off Loss vs. IC**

**TYPICAL CHARACTERISTICS – Half Bridge IGBT and Neutral Point Diode**




Figure 7. Typical Switching Times vs. IC




Figure 8. Typical Switching Times vs. IC




Figure 9. Typical Reverse Recovery Time vs. IC




Figure 10. Typical Reverse Recovery Charge vs. IC




Figure 11. Typical Reverse Recovery Peak Current vs. IC




Figure 12. Typical Diode Current Slope vs. IC

# NXH80T120L2Q0S1G

## TYPICAL CHARACTERISTICS – Half Bridge IGBT and Neutral Point Diode




Figure 13. Typical Reverse Recovery Time vs.  
IC




Figure 14. Gate Voltage vs. Gate Charge




Figure 15. IGBT Transient Thermal Impedance




Figure 16. Diode Transient Thermal Impedance

# NXH80T120L2Q0S1G

## TYPICAL CHARACTERISTICS – Neutral Point IGBT and Half Bridge Diode




Figure 17. IGBT Typical Output Characteristics




Figure 18. IGBT Typical Output Characteristics




Figure 19. IGBT Typical Transfer Characteristics




Figure 20. Diode Forward Characteristic




Figure 21. Typical Turn On Loss vs. IC




Figure 22. Typical Turn Off Loss vs. IC

# NXH80T120L2Q0S1G

## TYPICAL CHARACTERISTICS – Neutral Point IGBT and Half Bridge Diode




Figure 23. Typical Switching Times vs. IC




Figure 24. Typical Switching Times vs. IC




Figure 25. Typical Reverse Recovery Time vs. IC




Figure 26. Typical Reverse Recovery Charge vs. IC




Figure 27. Typical Reverse Recovery Peak Current vs. IC




Figure 28. Typical Diode Current Slope vs. IC

# NXH80T120L2Q0S1G

## TYPICAL CHARACTERISTICS – Neutral Point IGBT and Half Bridge Diode




Figure 29. Typical Reverse Recovery Energy vs. IC




Figure 30. Gate Voltage vs. Gate Charge




Figure 31. IGBT Transient Thermal Impedance




Figure 32. Diode Transient Thermal Impedance

# NXH80T120L2Q0S1G

## TYPICAL CHARACTERISTICS – Thermistor




Figure 33. Thermistor Characteristics

## ORDERING INFORMATION


Orderable Part Number	Marking	Package	Shipping
NXH80T120L2Q0S1G Q0PACK	NXH80T120L2Q0S1G	Q0PACK – Case 180AH (Pb-Free and Halide-Free)	24 Units / Blister Tray

# NXH80T120L2Q0S1G

## PACKAGE DIMENSIONS

### PIM18, 55x32.5 / Q0PACK

CASE 180AH  
ISSUE B



#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO THE PLATED TERMINALS AND IS MEASURED BETWEEN 1.00 AND 3.00 FROM THE TERMINAL TIP.
4. POSITION OF THE CENTER OF THE TERMINALS IS DETERMINED FROM DATUM B THE CENTER OF DIMENSION D, X DIRECTION, AND FROM DATUM A, Y DIRECTION. POSITIONAL TOLERANCE, AS NOTED IN DRAWING, APPLIES TO EACH TERMINAL IN BOTH DIRECTIONS.
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES.

DIM	MILLIMETERS	
	MIN.	NOM.
A	13.50	13.90
A1	0.10	0.30
A2	11.50	11.90
A3	15.65	16.05
A4	16.35	REF
b	0.95	1.05
D	54.80	55.20
D1	65.60	66.20
E	32.20	32.80
P	4.20	4.40
P1	8.90	9.10

#### MOUNTING HOLE POSITION

NOTE 4

PIN	PIN POSITION		PIN	PIN POSITION		PIN	PIN POSITION	
	X	Y		X	Y		X	Y
1	16.80	11.30	10	-14.10	-10.70	1	16.80	-11.30
2	13.80	11.30	11	-6.70	-10.70	2	13.80	-11.30
3	5.00	11.30	12	-4.00	-10.70	3	5.00	-11.30
4	2.30	11.30	13	2.30	-10.70	4	2.30	-11.30
5	-16.80	4.70	14	5.00	-10.70	5	-16.80	-4.70
6	-16.80	1.70	15	13.80	-10.70	6	-16.80	-1.70
7	-16.80	-1.30	16	16.80	-10.70	7	-16.80	1.30
8	-16.80	-4.30	17	16.80	-3.50	8	-16.80	4.30
9	-16.80	-10.70	18	16.80	3.10	9	-16.80	10.70





# NXH80T120L2Q0S1G

## PACKAGE DIMENSIONS

**PIM18, 55x32.5 / Q0PACK**  
**CASE 180AH**  
**ISSUE O**

### MOUNTING HOLE POSITION

PIN	PIN POSITION		PIN	PIN POSITION	
	X	Y		X	Y
1	16.80	11.30	10	-14.10	-10.70
2	13.80	11.30	11	-6.70	-10.70
3	5.00	11.30	12	-4.00	-10.70
4	2.30	11.30	13	2.30	-10.70
5	-16.80	4.70	14	5.00	-10.70
6	-16.80	1.70	15	13.80	-10.70
7	-16.80	-1.30	16	16.80	-10.70
8	-16.80	-4.30	17	16.80	-3.50
9	-16.80	-10.70	18	16.80	3.10



MOUNTING HOLE DETAIL

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative