


## 12 A - 800 V - 150 °C 8H Triac in TO-220AB



### Features

- 12 A medium current Triac
- 800 V symmetrical blocking voltage
- 150 °C maximum junction temperature  $T_j$
- Three triggering quadrants
- High noise immunity - static dV/dt
- Robust dynamic turn-off commutation - (dI/dt)c
- ECOPACK<sup>2</sup> compliant component
- Molding resin UL94-V0 flammability certified

### Applications

- General purpose AC line load control
- AC induction and universal motor control
- Lighting and automation I/O control
- Water heater, room heater and coffee machine
- Home automation smart AC plug
- Inrush current limiter in AC DC rectifiers

### Description

Specifically designed to operate at 800 V and 150 °C, the T1235H-8T Triac housed in TO-220AB provides an enhanced thermal management: this 12 A Triac is the right choice for a compact drive of heavy AC loads and enables the heatsink size reduction.

Based on the ST Snubberless high temperature technology, it offers higher specified turn off commutation and noise immunity levels up to the  $T_j$  max.

The T1235H-8T safely optimizes the control of the hardest universal motors, heaters and inductive loads for industrial control and home appliances.

Snubberless is a trademark of STMicroelectronics.

Product status link	
T1235H-8T	
Product summary	
I <sub>T(RMS)</sub>	12 A
V <sub>DRM/V<sub>RRM</sub></sub>	800 V
V <sub>DSM/V<sub>RSM</sub></sub>	900 V
I <sub>GT</sub>	35 mA
T <sub>j</sub> max.	150 °C

## 1 Characteristics

**Table 1. Absolute maximum ratings (limiting values)**

Symbol	Parameter	Value	Unit
$I_{T(RMS)}$	RMS on-state current (full sine wave)	12	A
$I_{TSM}$	Non repetitive surge peak on-state current (full cycle, $T_j$ initial = 25 °C)	$t = 16.7$ ms	126
		$t = 20$ ms	120
$I^2t$	$I^2t$ value for fusing	$t_p = 10$ ms	$A^2s$
$dI/dt$	Critical rate of rise of on-state current, $I_G = 2 \times I_{GT}$ , $t_r \leq 100$ ns, $f = 100$ Hz	$T_j = 25$ °C	$A/\mu s$
$V_{DRM}/V_{RRM}$	Repetitive peak off-state voltage	800	V
$V_{DSM}/V_{RSM}$	Non Repetitive peak off-state voltage	$t_p = 10$ ms, $T_j = 25$ °C	900
$I_{GM}$	Peak gate current	$t_p = 20$ μs, $T_j = 150$ °C	4
$P_{GM}$	Maximum gate power dissipation		5
$P_{G(AV)}$	Average gate power dissipation	$T_j = 150$ °C	1
$T_{stg}$	Storage temperature range	-40 to +150	°C
$T_j$	Operating junction temperature range	-40 to +150	°C
$T_L$	Maximum lead temperature for soldering during 10 s	260	°C

**Table 2. Electrical characteristics ( $T_j = 25$  °C, unless otherwise specified)**

Symbol	Test conditions	Quadrants		Value	Unit
$I_{GT}$	$V_D = 12$ V, $R_L = 30$ Ω	I - II - III	Min.	5	mA
			Max.	35	mA
$V_{GT}$	$V_D = 12$ V, $R_L = 30$ Ω	I - II - III	Max.	1.3	V
$V_{GD}$	$V_D = V_{DRM}$ , $R_L = 3.3$ kΩ	$T_j = 150$ °C	I - II - III	0.15	V
$I_L$	$I_G = 1.2 \times I_{GT}$	I - III	Max.	50	mA
		II	Max.	80	mA
$I_H$ <sup>(1)</sup>	$I_T = 500$ mA, gate open		Max.	35	mA
$dV/dt$ <sup>(1)</sup>	$V_D = V_R = 536$ V, gate open	$T_j = 150$ °C	Min.	2000	V/μs
$(dI/dt)c$ <sup>(1)</sup>	Without snubber network	$T_j = 150$ °C	Min.	12	A/ms

1. For both polarities of A2 referenced to A1.

**Table 3. Static characteristics**

Symbol	Test conditions	T <sub>j</sub>		Value	Unit
V <sub>TM</sub> <sup>(1)</sup>	I <sub>TM</sub> = 17 A, t <sub>p</sub> = 380 µs	25 °C	Max.	1.50	V
V <sub>TO</sub> <sup>(1)</sup>	Threshold voltage	150 °C	Max.	0.80	V
R <sub>D</sub> <sup>(1)</sup>	Dynamic resistance	150 °C	Max.	32	mΩ
I <sub>DRM</sub> /I <sub>RRM</sub>	V <sub>D</sub> = V <sub>R</sub> = V <sub>DRM</sub> = V <sub>RRM</sub>	25 °C	Max.	2.0	µA
		150°C		4.5	mA
	V <sub>D</sub> = V <sub>R</sub> = 400 V, peak voltage	150 °C	Max.	1.7	mA


1. For both polarities of A2 referenced to A1.

**Table 4. Thermal resistance**


Symbol	Parameter		Value	Unit
R <sub>th(j-c)</sub>	Junction to case (AC)	Max.	1.1	°C/W
R <sub>th(j-a)</sub>	Junction to ambient	Typ.	60	°C/W

## 1.1 Characteristics (curves)


**Figure 1. Maximum power dissipation versus on-state RMS current (full cycle)**




**Figure 2. On-state RMS current versus case temperature (full cycle)**




**Figure 3. On-state RMS current versus ambient temperature (free air convection)**




**Figure 4. On-state characteristics (maximum values)**




**Figure 5. Relative variation of thermal impedance versus pulse duration**




**Figure 6. Recommended maximum case-to-ambient thermal resistance versus ambient temperature for different peak off-state voltages**




**Figure 7. Relative variation of gate trigger voltage and current versus junction temperature (typical values)**




**Figure 8. Relative variation of holding current and latching current versus junction temperature (typical values)**




**Figure 9. Surge peak on-state current versus number of cycles**




**Figure 10. Non repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 10$  ms**




**Figure 11. Relative variation of static dV/dt immunity versus junction temperature**



**Figure 12. Relative variation of critical rate of decrease of main current versus junction temperature**



**Figure 13. Relative variation of leakage current versus junction temperature for different values of blocking voltage**




## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

### 2.1 TO-220AB package information

- Epoxy resin is halogen free and meets UL94 flammability standard, level V0
- Lead-free plating package leads
- Recommended torque: 0.4 to 0.6 N·m

Figure 14. TO-220AB package outline



(1)Resin gate position accepted in one of the two positions or in the symmetrical opposites.

Table 5. TO-220AB package mechanical data

Ref.	Dimensions					
	Millimeters			Inches <sup>(1)</sup>		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.20		15.90	0.5984		0.6260
a1		3.75			0.1476	
a2	13.00		14.00	0.5118		0.5512
B	10.00		10.40	0.3937		0.4094
b1	0.61		0.88	0.0240		0.0346
b2	1.23		1.32	0.0484		0.0520
C	4.40		4.60	0.1732		0.1811
c1	0.49		0.70	0.0193		0.0276
c2	2.40		2.72	0.0945		0.1071
e	2.40		2.70	0.0945		0.1063
F	6.20		6.60	0.2441		0.2598
I	3.73		3.88	0.1469		0.1528
L	2.65		2.95	0.1043		0.1161
I2	1.14		1.70	0.0449		0.0669
I3	1.14		1.70	0.0449		0.0669
I4	15.80	16.40	16.80	0.6220	0.6457	0.6614
M		2.6			0.1024	

1. Inch dimensions are for reference only.

### 3 Ordering information

Figure 15. Ordering information scheme




Table 6. Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
T1235H-8T	T1235H-8T	TO-220AB	2.1 g	50	Tube

## Revision history

**Table 7. Document revision history**

Date	Version	Changes
20-Nov-2020	1	Initial release.
16-Dec-2020	2	Updated general description.

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved