

STEALTH™ Rectifier

30 A, 600 V

ISL9R3060G2-F085

Description

The ISL9R3060G2-F085 is STEALTH diode optimized for low loss performance in high frequency hard switched applications. The STEALTH family exhibits low reverse recovery current (I_{RRM}) and exceptionally soft recovery under typical operating conditions.



This device is intended for use as a free wheeling or boost diode in power supplies and other power switching applications. The low I_{RRM} and short t_a phase reduce loss in switching transistors. The soft recovery minimizes ringing, expanding the range of conditions under which the diode may be operated without the use of additional snubber circuitry. Consider using the STEALTH diode with an SMPS IGBT to provide the most efficient and highest power density design at lower cost.

Features

- High Speed Switching ($t_{rr} = 31$ ns(Typ.) @ $I_F = 30$ A)
- Low Forward Voltage ($V_F = 2.4$ V(Max.) @ $I_F = 30$ A)
- Avalanche Energy Rated
- AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant


Applications

- Automotive DCDC converter
- Automotive On Board Charger
- Switching Power Supply
- Power Switching Circuits



TO-247-2LD
CASE 340CL

MARKING DIAGRAM



| | |
|---------|---------------------------|
| \$Y | = onsemi Logo |
| &Z | = Assembly Plant Code |
| &3 | = Date Code (Year & Week) |
| &K | = Lot Traceability Code |
| R3060G2 | = Specific Device Code |

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

ISL9R3060G2–F085

ABSOLUTE MAXIMUM RATINGS $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Ratings | Units |
|----------------|---|-------------|------------------|
| V_{RRM} | Peak Repetitive Reverse Voltage | 600 | V |
| V_{RWM} | Working Peak Reverse Voltage | 600 | V |
| V_R | DC Blocking Voltage | 600 | V |
| $I_{F(AV)}$ | Average Rectified Forward Current @ $T_C = 125^\circ\text{C}$ | 30 | A |
| I_{FSM} | Non-repetitive Peak Surge Current (Halfwave 1 Phase 60 Hz) | 325 | A |
| E_{AVL} | Avalanche Energy (1 A, 40 mH) | 20 | mJ |
| T_J, T_{STG} | Operating Junction and Storage Temperature | -55 to +175 | $^\circ\text{C}$ |

THERMAL CHARACTERISTICS $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Max | Units |
|-----------------|---|------|---------------------------|
| $R_{\theta JC}$ | Maximum Thermal Resistance, Junction to Case | 0.58 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JA}$ | Maximum Thermal Resistance, Junction to Ambient | 45 | $^\circ\text{C}/\text{W}$ |

PACKAGE MARKING AND ORDERING INFORMATION

| Device Marking | Device | Package | Tube | Quantity |
|----------------|------------------|---------|------|----------|
| R3060G2 | ISL9R3060G2–F085 | TO–247 | – | 30 |

ELECTRICAL CHARACTERISTICS $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Conditions | | Min. | Typ. | Max | Units |
|------------------------------|-------------------------------|--|---|------|-----------|---------|----------|
| I _R | Instantaneous Reverse Current | V _R = 600 V | T _C = 25°C | – | – | 100 | μA |
| | | | T _C = 175°C | – | – | 2 | mA |
| V _{FM} ¹ | Instantaneous Forward Voltage | I _F = 30 A | T _C = 25°C | – | 2.0 | 2.4 | V |
| | | | T _C = 175°C | – | 1.5 | 2.2 | V |
| t _{rr} ² | Reverse Recovery Time | I _F = 1 A, di/dt = 200 A/μs, V _{CC} = 390 V | T _C = 25°C | – | 23 | 35 | ns |
| | | I _F = 30 A, di/dt = 200 A/μs, V _{CC} = 390 V | T _C = 25°C T _C = 175°C | – | 31 135 | 45 – | ns ns |
| t _a | Reverse Recovery Time | I _F = 30 A, di/dt = 200 A/μs, V _{CC} = 390 V | T _C = 25°C | – | 18 | – | ns |
| t _b | Reverse Recovery Charge | | | – | 13 | – | ns |
| Q _{rr} | | | | – | 48 | – | nC |
| E _{AVL} | Avalanche Energy | I _{AV} = 1.0 A, L = 40 mH | | 20 | – | – | mJ |

1. Pulse: Test Pulse width = 300 μs , Duty Cycle = 2%.

2. Guaranteed by design.

TEST CIRCUIT WAVEFORMS







Figure 1. Test Circuit Waveforms

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 2. Typical Forward Voltage Drop vs. Forward Current




Figure 3. Typical Reverse Current vs. Reverse Voltage




Figure 4. Typical Junction Capacitance




Figure 5. Typical Reverse Recovery Time vs. di/dt




Figure 6. Typical Reverse Recovery Current vs. di/dt




Figure 7. Forward Current Derating Curve

ISL9R3060G2-F085




Figure 8. Reverse Recovery Charge





Figure 9. Transient Thermal Response Curve

TO-247-2LD
CASE 340CL
ISSUE A

DATE 03 DEC 2019



NOTES: UNLESS OTHERWISE SPECIFIED.

- A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

GENERIC
MARKING DIAGRAM*


XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "•", may or may not be present. Some products may not follow the Generic Marking.

| | | |
|-------------------------|--------------------|---|
| DOCUMENT NUMBER: | 98AON13850G | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | TO-247-2LD | PAGE 1 OF 1 |

onsemi and Onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales