




**Product:** [REVConnect Wall-Mount \(Empty\)](#) 

REVConnect Wall-Mount Connector Mount, 96-Port (Empty)

**Product Description**

The REVConnect Wall-Mount Connector Mount for 96-Ports comes unloaded

**Technical Specifications**

**Product Overview**

Suitable Applications:	IBDN System 4800,3600,2400,1200,10GX
------------------------	--------------------------------------

**Physical Characteristics (Overall)**

Height:	15.281 in
Width:	7.638 in
Depth:	11.12 in
Front Connection:	Flush
Packaging:	Individually packaged in a plastic bag.
Weight:	6 lbs

**Connectors**

**Materials**

Description	Material	Color
Fanning Strips	Lexan	Black
Mount	Steel	Black

**Construction and Dimensions**

Max Capacity:	96 Ports (6 REVConnect Connector Module of 16-Port each to be ordered separately)
---------------	---

**Temperature Range**

Installation Temperature Range:	-10°C To +60°C
Storage Temperature Range:	-40°C To +70°C

**Standards**

UL Rating:	UL1863
------------	--------

**Applicable Environmental and Other Programs**

Environmental Space:	Indoor
EU Directive 2002/95/EC (RoHS):	Yes

**Flammability, LSOH, Toxicity Testing**

Safety Listing:	c(UL)us Listed
-----------------	----------------

**Related Part Numbers**

Related Parts:	REVConnect wall termination kit, REVConnect wall connector mount, REVConnect wall cable dressing module, REVConnect cable management channel, REVConnect wall horizontal channel kit
----------------	--

**Variants**

Item #	Color	UPC
RVUXCMT96E	Black	611589237918

**Product Notes**

Included Parts:	2 Wood Screws; 6 Velcro cable tie; 1 installation guide
Notes:	Refer to Installation Guide PX106708 (English) or visit our web site at <a href="http://www.belden.com">http://www.belden.com</a>

**History**

Update and Revision:	Revision Number: 0.27 Revision Date: 11-14-2022
----------------------	---

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.