# Product data sheet Characteristics

# NSYSF18860T

# Spacial SF enclosure glazed door - assembled - 1800x800x600 mm





#### Main Range Spacial Extended range Spacial SF Application Multi-purpose **Product or Component** Suitable enclosure Type Enclosure nominal 70.87 in (1800 mm) height Enclosure nominal width 31.50 in (800 mm) Enclosure nominal 23.62 in (600 mm) depth **Enclosure mounting** Floor-standing Device composition 2 sliding rails 4 mounting plate bracket

1 locking system with handle door

1 structure

1 rear panel 1 roof

Complementary

Complementary		
Structure type	Perforated structure with a pitch of 25 mm  Vertical uprights joined with top and bottom frames  Formed from a single section  Panels and doors built into the structure	
Door type	Glass front	
Number of doors	Front 1	
Door opening side	Reversible 120 °)	
Lock type	4 points lock, handle with 5 mm double bar insert front door	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Sides of enclosure Rear Front	
Removable parts	Door by screws hinge Rear panel by screws Roof by screws Mounting plate bracket by screws Sliding rail by screws	
Material	Frame galvanised steel Uprights galvanised steel Door Securit glass Door sheet steel Panels sheet steel Hinge zamak Handle polyamide 6 with 30 % fibre glass	
Surface finish	Epoxy-polyester powder	
Color	Enclosure Gray RAL 7035) Handle Black RAL 9005)	
Net Weight	240.70 lb(US) (109.18 kg)	

### Environment

Standards	IEC 62208	
NEMA Degree of Protection	NEMA 3R/12	
IP degree of protection	IP55 IEC 60529	
IK degree of protection	IK08 IEC 62262	

### Ordering and shipping details

Category	80035-ENCLOSURE SYSTEMS FLOOR MOUNT
Discount Schedule	ES1
GTIN	3606485118635
Nbr. of units in pkg.	1
Package weight(Lbs)	245.65 lb(US) (111.424 kg)
Returnability	No
Country of origin	ES

# Packing Units

Unit Type of Package 1	PCE
Package 1 Height	76.38 in (194.0 cm)
Package 1 width	27.36 in (69.5 cm)
Package 1 Length	33.46 in (85.0 cm)

#### Offer Sustainability

Offer Sustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS  Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

### Contractual warranty

Warranty	1	8 months