
Product data sheet Characteristics

NSYMR86

Monobloc perforated plates H800xW600mm with universal perforations 11x26mm





Overview

Lead time	Usually Ships within 4 Weeks	
-----------	------------------------------	--

Main

Range	Spacial	
	·	
Accessory / separate part category	Mounting accessory	
Product or Component Type	Mounting plate	
Device Application	Multi-purpose	
Enclosure nominal dimensions	31.50 In (800 mm) 23.62 in (600 mm)	
	31.50 in (800 mm) 47.24 in (1200 mm)	
Mounting Location	Step slide	
-	Direct fixing on backstuds	
Mounting plate description	Telequick perforated	
Range compatibility	Spacial S3D	
	Spacial CRN	
	Spacial S3X	
	Thalassa PLM	
Quantity per Set	Set of 1	
Material	steel	
Surface Finish	Zinc coated	

Complementary

Fixing mode	Screwed on backstuds M8	
	By fixing element	
Height	29.53 in (750 mm)	
Width	21.69 in (551 mm)	
Depth	0.59 in (15 mm)	
Thickness	0.08 in (2 mm)	
Net Weight	6.97 lb(US) (3.16 kg)	
Number of slots	867	
Variant particularity	With enclosures H800 x W1200 Installation in rear of enclosure	
Cut-out dimensions	11 x 26 mm	

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480183768
Nbr. of units in pkg.	1
Package weight(Lbs)	7.01 lb(US) (3.18 kg)
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.79 in (2.0 cm)
Package 1 width	21.85 in (55.5 cm)
Package 1 Length	29.72 in (75.5 cm)
Unit Type of Package 2	PAM
Number of Units in Package 2	126
Package 2 Weight	945.78 lb(US) (429.0 kg)
Package 2 Height	35.43 in (90.0 cm)
Package 2 width	39.37 in (100.0 cm)
Package 2 Length	47.24 in (120.0 cm)

Offer Sustainability

onor ouclamacing	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty 18 months
