Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



AX105367 Faceplates and Panels - CAT6+ KCONN Vert. Mount



For more Information please call

1-800-Belden1



General Description: CAT6+ KeyConnect Vertical Mount Patch Panel, 8 Port, Black (Preloaded) Usage (Overall) Suitable Applications: IBDN System, 3600 CAT6+, TIA Category 6 Related Parts: CAT6+ Pre-Terminated Cable Assemblies and Modular Cords **Physical Characteristics (Connectivity)** Capacity Max. Capacity: 08 port, Keyconnect coupler, CAT6+ Access Front Connection: Flush **Dimensions** Dimensions: Height (in.) Width (in.) Depth (in.) 1.500 1.870 Materials Materials: FXU HD Frame | Plastic - UL94V-0 | Black Color Color: Black Weight Weight: 0.050 lbs. **Packaging** Packaging: Individually packaged in a plastic bag, shipped in cardboard box (50/box) **Mechanical Characteristics (Connectivity)** Footprint/Type: KeyConnect Plug / Jack Compatibility: RJ45 Storage Temperature Range: -10°C To +75°C -10°C To +60°C **Operating Temperature Range: Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs** EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 MII Order #39 (China RoHS): EUP 50 Suitability Suitability - Indoor: Yes

Page 1 of 2 11-10-2016

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



AX105367 Faceplates and Panels - CAT6+ KCONN Vert. Mount

Transmission Characteristics (Connectivity)

Notes (Overall)

Product Family

Part Numbers:

KeyConnect Products	Compatibility
KeyConnect LC Duplex adapter	YES
KeyConnect SC Simplex adapter	YES
KeyConnect ST adapter	YES
KeyConnect 10GX, Cat6+, Cat5e Modular jack	YES
KeyConnect 10GX, Cat6+ Modular coupler	YES (one way)
KeyConnect 10GX, Cat6+, Cat5e Shielded Modular jack	NO
KeyConnect 10GX Shielded Modular coupler	NO
KeyConnect BNC Coax module	YES
KeyConnect Video F Coax (Flush)module	NO
KeyConnect Video F Coax (Recessed) module	YES

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX105367	1 EA	0.280 LB			CAT6+ KCONN VERT.MOUNT

Revision Number: 0 Revision Date: 05-27-2015

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2 11-10-2016