NSYS3CM606020

HMI encl. Spacial S3CM. H600xW600xD200 IP54, IK10, RAL7035. Rear door.





Main

Range	Spacial
Product name	Spacial S3CM
Application	Human-machine dialogue application
Category	Control enclosure
Enclosure nominal height	23.62 in (600 mm)
Enclosure nominal width	23.62 in (600 mm)
Enclosure nominal depth	7.87 in (200 mm)
Installation accessory type	Suspension system
Product destination	Interface
Device composition	1 body 1 door with lock 2 rail 1 reinforcement plate 1 front trim frame 1 cable gland plate

Complementary

Body type	Single piece body
Door type	Solid
Number of doors	Rear 1
Door opening side	Reversible 120 °)
Lock type	3 mm double-bar lock
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Accessibility for operation	Rear
Removable parts	Door by hinges Trim frame by screws 2 rails by screws Cable gland plate by screws
Material	Enclosure and front face steel Trim frame aluminium
Surface finish	Epoxy-polyester powder
Color	Enclosure Gray RAL 7035) Front face Gray RAL 7040)
Net Weight	43.24 lb(US) (19.612 kg)

Environment

IP degree of protection	IP54 IEC 60529
IK degree of protection	IK10 IEC 62262

Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	3606480212895
Nbr. of units in pkg.	1
Package weight(Lbs)	43.24 lb(US) (19.612 kg)

Returnability	No
Country of origin	ES
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	24.41 in (62.0 cm)
Package 1 width	24.41 in (62.0 cm)
Package 1 Length	8.66 in (22.0 cm)
Offer Sustainability Sustainable offer status REACh Regulation	Green Premium product
	REACH Declaration
-	
REACh free of SVHC EU RoHS Directive	Yes
REACh free of SVHC EU RoHS Directive	Yes Pro-active compliance (Product out of EU RoHS legal scope) ☐EU RoHS
REACh free of SVHC	Yes Pro-active compliance (Product out of EU RoHS legal scope) ☐EU RoHS Declaration

Contractual warranty

Environmental Disclosure

Warranty	18 months

☑ China RoHS Declaration

Product Environmental Profile