



Order symbol: AR664CHSSLT
Product nbr: 8561036
Description: PC Enclosure
Remarks: Hinged transparent cover
w/S.S. Lockable latch

EAN: 6418074066688
El. number:
Finland:

Including: Hinged cover base with 10-32 brass inserts, latched cover with formed in place PUR gasket, and stainless hinge pin. Quick release latches. (Latch options available.) Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

Sample photo

Dimensions:			Accessories:		
mm:	152	152	102	ABP66	Painted Steel Back Panel
inch:	6.0	6.0	4.0	ALBP66	Aluminum Back Panel
			ADFP66	Dead Front Panel w/ screws	
Materials:			ASP66	Aluminum Swing Panel	
Material:	Polycarbonate		ASPK66	Swing Panel Kit incl. Panel	
Base colour:	RAL 7035 -light grey		ASPHK6	Swing Panel Kit w/o Panel	
Cover screws material:	Stainless steel		AMFL6	6" Mounting Flange Set	
Cover colour:	Clear transparent				
Gasket material:	Polyurethane				
Temperatures:			Rating:		
Temperature °C (short term):	-40 ... 140 °C		Ingress Protection (EN 60529): IP66/IP67		
Temperature °C (continuous):	-40 ... 80 °C		Impact Resistance (EN 62262): IK09		
Temperature °F (short term):	-40 ... 284 °F		Electrical insulation: Totally insulated		
Temperature °F (continuous):	-40 ... 175 °F		Halogen free (DIN/VDE 0472, Part 815): 0		
			UV resistance: UL 508		
			Flammability Rating: UL 508		
			Glow Wire Test (IEC 695-2-1) °C: 960		
			NEMA Class: UL Type 4, 4X, 6, 6P, 12 and 13		
Accessories:					
APBP66	PVC Back Panel				

