









Dimensions:
mm
[inches]

Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory (modshop@hammfg.com) for quotes
Solid models of this enclosure available in .stp or .x_t
(Part number and text placement/orientation on our products are subject to change,
we do not recommend using them as a locating reference for modification purposes)

NOTE

Purchased assembly includes Box, Lid, String Gasket, 4 PCB screws, and 4 Lid screws.

Recommended Torque : (43-50) Ozf.in / (30-35) cN.m

RZ Enclosure

Polycarbonate Off-White (UL94-V2)	RZ0214BF
Polycarbonate Off-White with Clear Lid (UL94-V2)	RZ0214BFC
General Purpose ABS Light Grey (UL94 HB)	RZ0313BF
General Purpose ABS Light Grey with Polycarbonate Clear Lid (UL94 HB)	RZ0313BFC

ACCESSORIES

Cover Screw (M4-0.7 X 20mm) (50 Pkg)	SC618-50
PCB Screw Self Tapping (M3 X 6mm) (50 Pkg)	SC622-50
String Gasket EPDM Grey (2 Pkg)	RZ0313GASKET

HAMMOND MANUFACTURING
RZ0214BF (0313BF)
www.hammondmfg.com