NSYSPCP

Cable ducting support to be used with 22mmdiameter products





Main	
Accessory / separate part category	Cable management accessory
Product or Component Type	Support
Product destination	Cable duct
Range compatibility	Thalassa PLA Thalassa PLS Thalassa PLM Spacial SBM Spacial S3D Spacial S3CM Spacial CRN
Anwendung	Multi-purpose
Mounting Support	Door

1 support

Set of 10

Complementary

Material	Galvanised steel	
Fixing mode	By screws on 22 mm equipment	
Height	3.94 in (100 mm)	
Width	1.18 in (30 mm)	
Depth	0.45 in (11.5 mm)	
Diameter	0.89 In (22.5 mm) 0.00 in (0 mm)	

Device composition

Quantity per Set

Ordering and shipping details

Ordering and shipping details	
Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480184482
Nbr. of units in pkg.	1
Package weight(Lbs)	1.06 oz (30.0 g)
Returnability	No
Country of origin	FR

Packing Units

1 doking office		
Unit Type of Package 1	PCE	
Package 1 Height	1.18 in (3 cm)	
Package 1 width	1.38 in (3.5 cm)	
Package 1 Length	4.33 in (11 cm)	
Unit Type of Package 2	BAG	
Number of Units in Package 2	10	
Package 2 Weight	10.62 oz (301.0 g)	
Package 2 Height	1.18 in (3 cm)	
Package 2 width	1.57 in (4 cm)	
Package 2 Length	4.33 in (11 cm)	
Unit Type of Package 3	S01	
Number of Units in Package 3	160	
Package 3 Weight	10.88 lb(US) (4.933 kg)	

Package 3 Height	5.91 in (15 cm)	
Package 3 width	5.91 in (15 cm)	
Package 3 Length	15.75 in (40 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	[™] China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months