



Product: 10GX KCON Cpl PP AngFlex 48 2U ☑

10GX KeyConnect Coupler Patch Panel AngleFlex 48P, UTP

# **Product Description**

AngleFlex Patch Panel, 48-port, 2U, with 10GX RJ45 Coupler

# **Technical Specifications**

### **Product Overview**

Suitable Applications:	IBDN System 10GX, TIA Category 6A, 10GBASE-T

## **Physical Characteristics (Overall)**

Height:	88.9 mm
Width:	482.600 mm
Depth:	78.740 mm
Port Count:	48 Port
Front Connection:	Angled
Packaging:	Individually packaged in a cardboard box.
Weight:	2.454 kg

## **Connectors**

### Materials

Description	Material	
Panel	Steel	

## **Construction and Dimensions**

Max Capacity:	48 connectors
' '	

## **Temperature Range**

Installation Temperature Range:	-10°C To +60°C
Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-10°C To +60°C

## **Mechanical Characteristics**

Footprint/Type:	KeyConnect		
-----------------	------------	--	--

## **Standards**

Data Category:	Category 6A

# **Applicable Environmental and Other Programs**

Environmental Space:	Indoor
EU Directive 2011/65/EU (RoHS 2):	Yes
MII Order #39 (China RoHS):	EUP 50

# Flammability, LS0H, Toxicity Testing

Safety Listing:	Bi-national Standard Listed
-----------------	-----------------------------

### **Related Part Numbers**

Poloted Porto:	Compatible with 10GX Patch Cord and 10GX Pre-Terminated Cable Assemblies
Related Parts:	Compatible with 10GX Patch Cord and 10GX Pre-Terminated Cable Assemblies

#### Variants

Item #	Color	UPC
AX104571	Black	611589006804

### **Product Notes**

Included Parts:	4 Screws (10x32); 4 Screws (12x24); 1 Printable LabelFlex Half-Sheet; 4 Velcro Straps; 4 Rear Cable Management Bracket, 1 Installation Guide
Notes:	For proper installation refer to Installation Guide PX104673 included with the product. Refer to AX104024 for the Specifications of the Couplers.

### **History**

Update and Revision:	Revision Number: 0.173 Revision Date: 03-14-2023

#### © 2023 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.