NSYS3CM806030

HMI encl. Spacial S3CM. H800xW600xD300IP54 IK10, RAL7035.Rear door.





Main

Range	Spacial	
Product name	Spacial S3CM	
Application	Human-machine dialogue application	
Category	Control enclosure	
Enclosure nominal height	31.50 in (800 mm)	
Enclosure nominal width	23.62 in (600 mm)	
Enclosure nominal depth	11.81 in (300 mm)	
Installation accessory type	Suspension system	
Product destination	Interface	
Device composition	1 body 1 door with lock 2 rail 1 reinforcement plate 1 front trim frame 1 cable gland plate	

Complementary

Body type	Single piece body	
Door type	Solid	
Number of doors	Rear 1	
Door opening side	Reversible 120 °)	
Lock type	3 mm double-bar lock	
Mounting plate description	Without mounting plate	
Type of gland plate	Standard	
Accessibility for operation	Rear	
Removable parts	Door by hinges Trim frame by screws 2 rails by screws Cable gland plate by screws	
Material	Enclosure and front face steel Trim frame aluminium	
Surface finish	Epoxy-polyester powder	
Color	Enclosure Gray RAL 7035) Front face Gray RAL 7040)	
Net Weight	64.17 lb(US) (29.106 kg)	

Environment

IP degree of protection	IP54 IEC 60529
IK degree of protection	IK10 IEC 62262

Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	3606480212871
Nbr. of units in pkg.	1
Package weight(Lbs)	64.17 lb(US) (29.106 kg)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	32.28 in (82.0 cm)
Package 1 width	24.41 in (62.0 cm)
Package 1 Length	12.60 in (32.0 cm)

Offer Sustainability

Green Premium product REACh Declaration Yes Pro-active compliance (Product out of EU RoHS legal scope) LU RoHS
Yes
<u>_</u>
Pro-active compliance (Product out of EU RoHS legal scope) GEU RoHS
Declaration
Yes
₫Yes
☑ China RoHS Declaration
Product Environmental Profile

Contractual warranty

Warranty	18 months	