

EnviroSense2 (E2) Environmental Sensor Module, Temperature, TAA

MODEL NUMBER: E2MT



Monitors ambient temperature conditions.

Description

The E2MT E2 Environmental Sensor Module works with LX Platform devices, including WEBCARDLX, WEBCARDLXE, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs. By connecting the included USB cable to an LX Platform device, the E2MT allows you to remotely monitor ambient temperature conditions in network environments.

If temperature values exceed a certain limit, it is recorded in the event log of the LX Platform device's PowerAlert® Device Manager interface. The E2MT mounts magnetically to most racks and cabinets. Up to three E2 modules can be daisy-chained together. A built-in retention harness secures cable connections to reduce clutter.

Features

Compatible with LX Platform Devices Compatible devices include WEBCARDLX, WEBCARDLXE, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs Measures and monitors ambient temperature

Easy to Install and Operate Attaches magnetically to most racks and cabinets Up to 3 E2 modules can be daisy-chained together Built-in cable harness reduces clutter USB cable included Compatible with free downloadable PowerAlert software

Highlights

- Compatible with LX Platform devices
- Easy magnetic mounting to most racks and cabinets
- Up to 3 E2 modules can be daisy-chained together
- Built-in cable harness reduces clutter
- USB cable included

Package Includes

- E2MT EnviroSense2 Environmental Sensor Module
- USB cable (A to Micro-B), 3 ft.
- Owner's manual

Specifications

| OVERVIEW | |
|----------------------|----------------------|
| UPC Code | 037332196293 |
| CONNECTIONS | |
| Side A - Connector 1 | USB A (FEMALE) |
| Side B - Connector 1 | MICRO-USB B (FEMALE) |
| PHYSICAL | |



Powering Business Worldwide

TRIPP LITE
SERIES

| | |
|--------------------------------------|--------------------------------------|
| Cable Length (ft.) | 3 |
| Cable Length (m) | 0.91 |
| Shipping Dimensions (hwd / in.) | 1.10 x 4.20 x 5.90 |
| Shipping Dimensions (hwd / cm) | 2.79 x 10.67 x 14.99 |
| Shipping Weight (lbs.) | 0.28 |
| Shipping Weight (kg) | 0.13 |
| Unit Dimensions (hwd / in.) | 0.830 x 2.520 x 1.420 |
| COMMUNICATIONS | |
| Product Compatibility | WEBCARDLX; WEBCARDLXMINI; WEBCARDLXE |
| FEATURES & SPECIFICATIONS | |
| Sensing Capability | Temperature |
| Contact Closure Capability | Contact Closure Input Monitoring |
| STANDARDS & COMPLIANCE | |
| Product Compliance | Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.