NSYS3D12830P

Spacial S3D plain door with mount.plate. H1200xW800xD300 IP66 IK10 RAL7035.





Main	
Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	47.24 in (1200 mm)
Enclosure nominal width	31.50 in (800 mm)
Enclosure nominal depth	11.81 in (300 mm)
Door type	Solid
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 2 cable gland plate 1 mounting plate 1 door with lock

Complementary

Body type	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face 1	
Door opening side	Reversible 120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure steel Mounting plate galvanised steel	
Surface finish	Enclosure epoxy-polyester powder	
Color	Enclosure Gray RAL 7035)	
Standards	IEC 62208	
Product Certifications	CUL LR DNV GL UL BV	
Net Weight	134.48 lb(US) (61 kg)	

Environment

NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP66 IEC 60529

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480159879
Nbr. of units in pkg.	1
Package weight(Lbs)	114.51 lb(US) (51.943 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	13.78 in (35 cm)
Package 1 width	32.28 in (82 cm)
Package 1 Length	48.23 in (122.5 cm)

Offer Sustainability

- · · · · · · · · · · · · · · · · · · ·	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

· · · · · · · · · · · · · · · · · · ·	
Warranty	18 months