



**Product:** [10GX REVConnect Cpl PP 24 1U](#)

10GX REVConnect Coupler Patch Panel 24 Port 1U, UTP



**Product Description**

10GX REVConnect Pre-Loaded Coupler Patch Panel, 24-port, 1U

**Technical Specifications**

**Product Overview**

Suitable Applications:	10GX Systems, TIA Category 6A, ISO Class EA, 10GBASE-T
------------------------	--

**Physical Characteristics (Overall)**

Height:	1.730 in
Width:	19.000 in
Depth:	2.000 in
Port Count:	24 Port
Front Connection:	Flush
Packaging:	Individually packaged in a cardboard box.
Weight:	1.646 lbs

**Connectors**

**Materials**

Description	Material
Panel	Steel

**Construction and Dimensions**

Max Capacity:	24 connectors (patch panel is pre-loaded)
---------------	---

**Electrical Characteristics**

Dielectric Strength:	1,000 V RMS @ 60Hz for 1 minute
Current Rating:	1.300 A
Insulation Resistance:	500 M-Ohm Minimum
Termination Resistance:	2.5 mOhm

**Temperature Range**

Installation Temperature Range:	-10°C To +60°C
Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-10°C To +60°C

**Mechanical Characteristics**

Footprint/Type:	REVConnect
Plug /Jack Compatibility:	RJ45, REVConnect Core
Termination Type:	Universal T568A/B

**Standards**

UL Rating:	UL94 V-0
Data Category:	Category 6A
TIA/EIA Compliance:	Category 6A - TIA 568.C.2, Category 6A - ISO/IEC 11801:2002 Ed.2
Other Standards:	FCC Part 68, Subpart F, IEC 60603-7

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU Directive 2011/65/EU (RoHS 2):	Yes
MII Order #39 (China RoHS):	EUP 50

Flammability, LS0H, Toxicity Testing

Safety Listing:	c(UL)us Listed
-----------------	----------------

Related Part Numbers

Related Parts:	10GX REVConnect Modular Couplers, 10GX RevConnect Cords
----------------	---

Variants

Item #	Color	Put-Up Type	UPC
RVACPF1U24BK	Black	1U	611589247467

Product Notes

Included Parts:	24 10GX REVConnect Couplers, Black; 25 REVConnect Cable Managers and Term; 4 Clear Windows;1 Rear Cable Management Bar; 4 Screws (10x32); 4 Screws (12x24); 2 Velcro Straps; 4 Frames; 1 Installation Guide
Notes:	For proper installation refer to Installation Guide PX106520 included with the product or visit our web site at <a href="http://www.belden.com">http://www.belden.com</a>

History

Update and Revision:	Revision Number: 0.18 Revision Date: 05-10-2023
----------------------	---

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.