HAMMOND

Quality Products. Service Excellence.

Type 4X Stainless Steel Two Door Freestanding Enclosure *HN4 FSTD SS Series*

Continuous Hinge Door with Handle

NEW

Panel Sold Separately

Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.

Construction

- Formed 12 gauge 304 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- Dual Access versions have doors front and back.
- 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Center post is removable for easy installation of the inner panel.

Standards

- UL 508A Type 3R, 4X and 12
- CSA Type 3R, 4X and 12
- Complies with:
  - NEMA Type 3R, 4X, 12 and 13
  - IEC 60529, IP66

Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.

Accessories

- Inner Panels
- Panel Rails
- Door Stop Kit
- Drip Shield Kit
- Window Kits
- Lighting
- Center Panel Supports
- Swing Out Frames
- Top Hat Cable Modules
- Type 12/4, 4X Handle Kits
- Climate Control
- General Accessories

Single Access

	Enclosure			
Part No.	H	W	D	Optional Full Panel[1]
HN4FS604818SS	60.00	48.00	18.00	**60AWFW**
HN4FS724818SS	72.00	48.00	18.00	**72ZWFW**

	Enclosure			
Part No.	H	W	D	Optional Full Panel[1]
HN4FS726018SS	72.00	60.00	18.00	**72ZXFW**
HN4FS727218SS	72.00	72.00	18.00	**72ZYFW**
HN4FS904820SS	90.00	48.00	20.00	**90BWFW**
HN4FS907220SS	90.00	72.00	20.00	**90BYFW**
HN4FS724824SS	72.00	48.00	24.00	**72ZWFW**
HN4FS726024SS	72.00	60.00	24.00	**72ZXFW**
HN4FS727224SS	72.00	72.00	24.00	**72ZYFW**
HN4FS907224SS	90.00	72.00	24.00	**90BYFW**
HN4FS726036SS	72.00	60.00	36.00	**72ZXFW**
HN4FS907236SS	90.00	72.00	36.00	**90BYFW**

[1] Refers to optional full height/full width panels. Depth panels/half height width panels are also available

Dual Access

	Enclosure			
Part No.	H	W	D	Optional Full Panel[1]
HN4FS724824DASS	72.00	48.00	24.00	**72ZWFW**
HN4FS726024DASS	72.00	60.00	24.00	**72ZXFW**
HN4FS727224DASS	72.00	72.00	24.00	**72ZYFW**
HN4FS907224DASS	90.00	72.00	24.00	**90BYFW**
HN4FS726036DASS	72.00	60.00	36.00	**72ZXFW**

[1] Refers to optional full height/full width panels. Depth panels/half height width panels are also available

Tags: **HN4FS**, **freestanding**, **stainless**, **stainless steel**, **304**, **control box**, **Type 4X**, **two door**, **NEMA 4X**, **continuous hinge**, **handle**, **corrosion**

Data subject to change without notice

© 2025. Hammond Manufacturing Ltd. All rights reserved.