



# Wall-Mount Fiber Optic Distribution Enclosure, 4-Panel Capacity

MODEL NUMBER: N492-WM4-BK











Convenient, secure and fully sealed wall-mount fiber optic enclosure for managing and protecting your fiber terminations. Compatible with Tripp Lite high-density fiber adapter panels.

#### **Description**

The N492-WM4-BK Wall-Mount Fiber Optic Distribution Enclosure manages and protects your fiber terminations where space is at a premium. It locks using the included key to keep your connections safe from tampering. The doors open wide to reveal plenty of room for splicing and patching your fiber cabling. It supports up to four fiber adapter panels, such as high-density LC (N492-08D-LC), SC (N492-06D-SC) and ST (N492-08S-ST) panels. Cable manager rings, cable ties and a labeling sticker help you keep your cables neatly organized inside the fully sealed enclosure. Made from heavy-duty cold-rolled steel, the N492-WM4-BK mounts on any solid surface.

### **Features**

# Fully Sealed Enclosure Manages and Protects Your Fiber Terminations

- Patch and splice cabling in a single enclosure
- Mounts securely on any solid surface
- Locks with included key to protect connections against tampering
- Heavy-duty cold-rolled steel construction
- Cable manager rings, cable ties and label included for organized cable management
- Supports up to 4 fiber adapter panels, including N492-08D-LC, N492-06D-SC and N492-08S-ST

# **Specifications**

OVERVIEW		
UPC Code	037332202925	
Technology	Multimode; Singlemode	
Country/Region	Global	
PHYSICAL		

## **Highlights**

- Mounts securely on any solid surface
- Locks with included key to protect connections against tampering
- Made from heavy-duty coldrolled steel
- Includes rings, ties and label for organized cable management
- Supports up to 4 fiber adapter panels

#### **Package Includes**

- N492-WM4-BK Wall-Mount Fiber Optic Distribution Enclosure, 4-Panel Capacity
- (4) Cable manager rings
- (5) Cable ties
- Cable lock post
- Label
- (2) Keys
- Quick Start Guide





Color	Black	
Total Number of Ports	0	
Shipping Dimensions (hwd / in.)	6.70 x 18.70 x 14.50	
Shipping Dimensions (hwd / cm)	17.02 x 47.50 x 36.83	
Shipping Weight (lbs.)	12.80	
Shipping Weight (kg)	5.81	
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000	
Unit Dimensions (hwd / cm)	29 x 36.3 x 10.7	
Panel Style	Cassette Type	
ENVIRONMENTAL		
Operating Temperature	-40 to 140 F (-40 to 60 C)	
FEATURES & SPECIFICATIONS		
Antibacterial	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.