



Specifications

Standard Document

ANSI/ESD S20.20

Electrical Properties

Tab to floor contact point
Three layer rubber

- Outer Layer
- Middle Layer
- Inner Layer

Typical Values

1×10^6 to $< 1 \times 10^8$ ohms

- $< 1 \times 10^8$ ohms
- $< 1 \times 10^6$ ohms
- $< 1 \times 10^8$ ohms

Physical Properties

Construction:

Three layer non-marring rubber, yellow inner and outer dissipative layer and black conductive inner layer

Thickness:

0.060" (1.52 mm)

Color**:

Yellow

Texture**:

Embossed

**Color and texture may vary between lots and mills

Features

- A. Non-marring, solid, three layer rubber material
- B. Replaceable 3/8" wide, 18" long blue nylon ribbon contain 8 electrically conductive carbon suffused fibers, reversible, may be positioned on either side of the foot. Connect with 4mm snap
- C. Black 1/8" diameter stretchable nylon cord
- D. Adjustable slide lock
- E. 4mm solid stainless steel male snap to attach conductive ribbon

Note:

Two foot grounders are recommended for reliable grounding and ESD protection, providing ground when one foot is off the floor.

Operator is grounded when foot is in contact with grounded dissipative or conductive flooring.

For additional information on the use and maintenance of foot grounders, refer to Technical Bulletin [TB-2020](#).

For additional information on verifying the functionality of foot grounders, refer to Technical Bulletin [TB-3069](#).

See the Desco Industries Regulatory Statement:

DescoIndustries.com/pdf/Regulatory.pdf

See the Desco Limited Warranty:

Desco.com/Limited-Warranty.aspx

See the Desco Disclaimer:

Desco.com/Disclaimer.aspx



Made in the
United States of America

Item #	Description	Mens Shoe Size (Recommended)	Womens Shoe Size (Recommended)
17255	Small/Medium	6 – 9	6 – 10
17256	Large/XLarge	9 – 13	10 – 13
17257	Conductive Ribbon, 10 Pack		

U.S. Patent 12,041,708

Specifications and procedures subject to change without notice.

Unless otherwise specified tolerances are +/- 1/4"

DESCO

Shock Cord Foot Grounder

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com
PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
PHONE (781) 821-8370

**DRAWING
NUMBER**
17255

DATE:
July 2024